

Prüfbericht 366-0530-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000818

ANLAGE: 9.5
 Hersteller: MW Aftermarket Srl

Radtyp: 15604098-7
 Stand: 14.01.2016



Seite: 1 von 2

Manufacturer : CITROEN, FIAT, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 44
 Hole circle (mm)/number of holes : 98/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1681	R1-1681	Without	58		510	1894	47/14
R1-1682	R1-1682	Without	58		510	1894	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : A; 225L

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : A

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN NEMO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
A	e3*2001/116*0273*..	50 -55	185/65R15 88		
A	e3*2007/46*0013*..	50 -55	185/65R15 88		
225L	N130	50 -54	185/65R15 88		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm for Type : 225; 225L
 100 Nm for Type : 323

commercial type: **FIAT FIORINO, QUBO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
225	e3*2001/116*0271*..	51 -70	185/65R15 88		
225	e3*2007/46*0011*..	51 -70	185/65R15 88		
225L	N157	54 -55	185/65R15 88		

Prüfbericht 366-0530-15-WIRD/N1

zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000818

ANLAGE: 9.5

Hersteller: MW Aftermarket Srl

Radtyp: 15604098-7

Stand: 14.01.2016



Seite: 2 von 2

commercial type: **FIAT LINEA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
323	e3*2001/116*0260*..	57 -80	185/65R15 88		
			185/65R15-84		
		57 -94	195/60R15-88H		
		88 -94	185/65R15-88H		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : A; 225L; A*****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : A*****; A

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT BIPPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
A	e3*2001/116*0272*..	50 -55	185/65R15 88		
A*****	e3*2001/116*0272*..				
A	e3*2007/46*0012*..	50 -55	185/65R15 88		
225L	N127	50 -54	185/65R15 88		

Restrictions