

Prüfbericht 366-0515-15-WIRD
zur Erteilung der ECE (E1) 124R- 000822

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 14554100-15

Stand: 30.06.2015



Seite: 1 von 2

Manufacturer : RENAULT**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 CH Off set(mm) : 36

Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1132	R1-1132	Without	60		460	1780	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm for Type : BA; DA; EA; LA
100 Nm for Type : B; C06; JAcommercial type: **RENAULT CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B	e2*93/81*0126*..	40-66	165/65R14		1); 2); 33)
		47-66	175/65R14		
		66	175/60R14		
B	e2*98/14*0126*..	42-80	175/65R14 82		*); CLIO (Hatchback); THALIA (Stufenheck); 1); 2); 33)
		43-72	165/65R14 79		
		55-72	175/60R14-78		
		55-79	185/60R14-82H		

commercial type: **RENAULT MEGANE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BA	e2*93/81*0010*..	47-84	175/65R14		1); 2); 33)
		66-72	175/70R14		
			185/65R14		
		66-84	185/60R14		
BA	e2*98/14*0010*..	47-72	175/70R14 84		1); 2); 33)
		47-84	175/65R14 82		
		66-72	185/65R14		
		66-84	185/60R14		
DA	e2*93/81*0009*..	66-72	175/70R14		1); 2); 33)
			185/65R14		
		66-84	175/65R14		
			80-84	185/60R14	
DA	e2*98/14*0009*..	66-84	175/65R14		1); 2); 33)
		72	175/70R14		
			185/65R14		
		80-84	185/60R14		
EA	e2*93/81*0103*..	66-84	175/65R14		1); 2); 33)
		84	185/60R14		

Prüfbericht 366-0515-15-WIRD
zur Erteilung der ECE (E1) 124R- 000822

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 14554100-15

Stand: 30.06.2015



Seite: 2 von 2

commercial type: **RENAULT MEGANE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
EA	e2*98/14*0103*..	66 -84	175/65R14		1); 2); 33)
		80 -84	185/60R14		
LA	e2*93/81*0072*..	47 -84	175/65R14		1); 2); 33)
		66 -72	175/70R14		
			185/65R14		
66 -84	185/60R14				
LA	e2*98/14*0072*..	47 -70	175/65R14		1); 2); 33)
			175/70R14-82		
		66 -72	185/65R14		
		66 -84	185/60R14		
		70	175/70R14 84		

commercial type: **RENAULT MEGANE SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA	e2*93/81*0068*..	55 -66	175/70R14		1); 2); 33)
JA	e2*98/14*0068*..	55 -66	175/70R14		1); 2); 33)

commercial type: **RENAULT TWINGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C06	e2*98/14*0071*..	43 -55	155/65R14 75		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.