

**Prüfbericht 366-0515-15-WIRD
zur Erteilung der ECE (E1) 124R- 000822**

ANLAGE: 9.6

Hersteller: MW Aftermarket Srl

Radtyp: 14554100-15

Stand: 30.06.2015



Seite: 1 von 1

Manufacturer : HYUNDAI Assan Otomotiv Sanayi

Wheel dates:

Wheel size according to standard : 5 1/2 J X 14 CH Off set(mm) : 47

Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1903 | R1-1903 | Without | 54 | | 428 | 1781 | 47/14 |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : HYUNDAI Assan Otomotiv Sanayi

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **Hyundai i10**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|-------|-----------|-----------------------|--------------|
| IA | e11*2007/46*1008*.. | 49-64 | 175/65R14 | | 1); 2); 33) |

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.