

**Prüfbericht 366-0525-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000823**

**ANLAGE: 9.2**  
Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16  
Stand: 15.04.2015



Seite: 1 von 1

**Manufacturer : TOYOTA**

**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 15 CH Off set(mm) : 45  
Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1607	R1-1607	Without	54		448	1840	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : TOYOTA**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 103 Nm for Type : XP9(a); XP9F(a)  
110 Nm for Type : P1

commercial type: **TOYOTA YARIS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P1	e6*2001/116*0064*..	77	185/55R15-81V		1); 2); 33)
P1	e6*98/14*0064*..	77 -78	185/55R15-81V		*) ; 3-türig; 5-türig; Front wheel drive; 1); 2); 33)

commercial type: **Toyota Yaris, Daihatsu Charade**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
XP9(a)	e11*2001/116*0248*..	51 -98	185/60R15 84H		1); 2); 33)
XP9F(a)	e11*2001/116*0249*..	51 -74	185/60R15 84H		1); 2); 33)
XP9F(a)	e11*2001/116*0249*..	51 -66	185/60R15 84H		1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0525-15-WIRD/N2**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823**

**ANLAGE: 9.8**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16  
 Stand: 28.10.2015



Seite: 1 von 1

**Manufacturer : NISSAN EUROPE (F)**

**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 15 H2      Off set(mm) : 45  
 Hole circle (mm)/number of holes : 100/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1630	R1-1630	Without	60		451	1895	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : NISSAN EUROPE (F)**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 110 Nm

commercial type: **NISSAN NOTE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E11	e11*2001/116*0268*..	50-81	175/65R15 80		*); NOTE; 1); 2); 33)
			175/65R15 81		
			185/65R15 80		
			185/65R15 81		
		65-81	175/65R15 78		
			185/65R15 78		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.