

Prüfbericht 366-0525-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823

ANLAGE: 9.5
 Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16
 Stand: 26.08.2015



Seite: 1 von 1

Manufacturer : NISSAN

Wheel dates:

Wheel size according to standard : 5 1/2 J X 15 H2 Off set(mm) : 50
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1435	R1-1435	Without	60		451	1857	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : NISSAN

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad, for Type : K13
 Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : K12
 Accessories : Serie
 Tightening torque for fixing parts : 100 Nm for Type : K13
 113 Nm for Type : K12

commercial type: **NISSAN MICRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
K12	e11*2001/116*0195*..	48 -60	175/65R15 81		1); 2); 33)
		48 -65	175/60R15 81		
		48 -81	175/60R15		
		63 -81	175/65R15 80		
K13	e13*2007/46*1111*..	59 -72	175/60R15 81H		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

Prüfbericht 366-0525-15-WIRD/N2
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823

ANLAGE: 9.9
 Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16
 Stand: 28.10.2015



Seite: 1 von 2

Manufacturer : OPEL / VAUXHALL, SUZUKI

Wheel dates:

Wheel size according to standard : 5 1/2 J X 15 CH Off set(mm) : 50
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1717	R1-1717	Without	54		425	1840	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : OPEL / VAUXHALL

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 110 Nm

commercial type: **AGILA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
H-B	e4*2001/116*0135*..	48-69	185/60R15 84H		*) ; Front wheel drive; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SUZUKI

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : EX

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : EX

Tightening torque for fixing parts : 85 Nm

commercial type: **SPLASH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
EX	e4*2001/116*0130*..	48-69	185/60R15 84H		1); 2); 33)
EX	e4*2007/46*0283*..	66-69	185/60R15 84H		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- To be kept:
 - the standard wheel size and offset.

Prüfbericht 366-0525-15-WIRD/N2
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823

ANLAGE: 9.9
Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16
Stand: 28.10.2015



Seite: 2 von 2

- tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.