

**Prüfbericht 366-0559-15-WIRD
zur Erteilung der ECE (E1) 124R- 000826**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16654100-21

Stand: 01.06.2015



Seite: 1 von 1

Manufacturer : RENAULT**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 49
Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1468	R1-1468	Without	60		615	1989	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : M

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : JM

Tightening torque for fixing parts : 110 Nm for Type : M
130 Nm for Type : JM

commercial type: **RENAULT MEGANE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
M	e2*98/14*0272*..	60-99	205/55R16 91H		1); 2); 33)
		60-120	205/55R16 91V		

commercial type: **RENAULT SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JM	e2*2001/116*0274*..	60-83	205/55R16 91H		1); 2); 33)
			205/55R16 91V		
		74-120	205/60R16 92H		
			205/60R16 92V		
110	205/60R16 96				

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.