

**Prüfbericht 366-0531-15-WIRD
zur Erteilung der ECE (E1) 124R- 000827**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23

Stand: 27.03.2015



Seite: 1 von 1

Manufacturer : AUTOMOBILES DACIA S.A.

Wheel dates:

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 40

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1845	R1-1845	Without	60		588	1894	47/14
R1-1870	R1-1870	Without	60		588	1894	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : AUTOMOBILES DACIA S.A.

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2001/116*0314*..	61 -85	185/65R15 88		*) ; Only Lodgy; 1); 2); 33)
SD	e2*2001/116*0314*..	55 -85	185/65R15 88		*) ; Dokker; Station wagon; Box wagon; Front wheel drive; 1); 2); 33)
SD	e2*2007/46*0030*..	55 -66	185/65R15 92		*) ; only Dokker; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

Prüfbericht 366-0531-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.5
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 17.09.2015



Seite: 1 von 1

Manufacturer : RENAULT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 40
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1855	R1-1855	Without	60		460	1897	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **CLIO, CAPTUR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R	e2*2001/116*0327*..	48 -66	185/65R15 M+S		*); only Clio 4 from Mj. 2012; station wagonlimousine; Hatchback; not Captur; 1); 2); 33)
			185/65R15 88		
R	e2*2001/116*0327*..	54 -66	185/65R15 M+S		*); Grandtour; from NT*50; 1); 2); 33)
			185/65R15 88		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

Prüfbericht 366-0531-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.6
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 17.09.2015



Seite: 1 von 1

Manufacturer : **RENAULT**

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 40
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1865	R1-1865	Without	60		540	1897	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **ZOE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AG	e2*2007/46*0251*..	43	185/65R15 88		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

Prüfbericht 366-0531-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.7
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 17.09.2015



Seite: 1 von 2

Manufacturer : AUTOMOBILES DACIA S.A.

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 40
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1873	R1-1873	Without	60		450	1894	47/14
R1-1874	R1-1874	Without	60		450	1894	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : AUTOMOBILES DACIA S.A.

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2001/116*0314*..	53-66	185/65R15 88		*) Sandero (Hatchback) from Mj2013; 1); 2); 33)
SD	e2*2001/116*0314*..	55-77	185/65R15 88		*) Logan (Stufenheck) from Mj 2013; 1); 2); 33)
SD	e2*2007/46*0030*..	55-66	185/65R15		*) Sandero (Hatchback) from Mj2013; Front wheel drive; 1); 2); 33)
SD	e2*2007/46*0030*..	55-66	185/65R15 88		*) Logan (Stufenheck) from Mj 2013; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0531-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

ANLAGE: 9.7
Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
Stand: 17.09.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.