

Prüfbericht 366-0531-15-WIRD
zur Erteilung der ECE (E1) 124R- 000827

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23

Stand: 27.03.2015



Seite: 1 von 2

Manufacturer : RENAULT**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 43

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1350	R1-1350	Without	60		525	1895	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad,
for Type : DA; LA; KA; EA; BA; JA

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : B

Tightening torque for fixing parts : 90 Nm for Type : BA; DA; EA; LA
100 Nm for Type : B; JA; KA

commercial type: **RENAULT CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B	e2*98/14*0126*..	42 -79	185/55R15-81H		*); CLIO (Hatchback); THALIA (Stufenheck); 1); 2); 33)
		79 -124	185/55R15-81H M+S		

commercial type: **RENAULT MEGANE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BA	e2*98/14*0010*..	59 -85	185/60R15 84H		1); 2); 33)
DA	e2*98/14*0009*..	70	185/55R15-81H		1); 2); 33)
			185/55R15-81V		
		70 -84	185/60R15 84H		
		101 -108	185/55R15 M+S		
EA	e2*98/14*0103*..	70	185/55R15-81H		1); 2); 33)
			72 -84	185/60R15 84H	
		101 -108	185/55R15 M+S		
KA	e2*98/14*0192*..	59 -85	185/60R15 84H		1); 2); 33)
LA	e2*98/14*0072*..	59 -85	185/60R15 84H		1); 2); 33)

commercial type: **RENAULT MEGANE SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA	e2*93/81*0068*..	47 -84	185/65R15		1); 2); 33)

**Prüfbericht 366-0531-15-WIRD
zur Erteilung der ECE (E1) 124R- 000827**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23

Stand: 27.03.2015



Seite: 2 von 2

commercial type: **RENAULT MEGANE SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA	e2*98/14*0068*..	47 -85	185/65R15		1); 2); 33)
		59 -102	205/55R15		
		102 -103	195/60R15		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.