

**Prüfbericht 366-0531-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000827**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23

Stand: 27.03.2015



Seite: 1 von 2

**Manufacturer : RENAULT****Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 43

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1350	R1-1350	Without	60		525	1895	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad,  
for Type : DA; LA; KA; EA; BA; JA

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : B

Tightening torque for fixing parts : 90 Nm for Type : BA; DA; EA; LA  
100 Nm for Type : B; JA; KA

commercial type: **RENAULT CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B	e2*98/14*0126*..	42 -79	185/55R15-81H		*); CLIO (Hatchback); THALIA  (Stufenheck); 1); 2); 33)
		79 -124	185/55R15-81H M+S		

commercial type: **RENAULT MEGANE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BA	e2*98/14*0010*..	59 -85	185/60R15 84H		1); 2); 33)
DA	e2*98/14*0009*..	70	185/55R15-81H		1); 2); 33)
			185/55R15-81V		
		70 -84	185/60R15 84H		
		101 -108	185/55R15 M+S		
EA	e2*98/14*0103*..	70	185/55R15-81H		1); 2); 33)
			72 -84	185/60R15 84H	
		101 -108	185/55R15 M+S		
KA	e2*98/14*0192*..	59 -85	185/60R15 84H		1); 2); 33)
LA	e2*98/14*0072*..	59 -85	185/60R15 84H		1); 2); 33)

commercial type: **RENAULT MEGANE SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA	e2*93/81*0068*..	47 -84	185/65R15		1); 2); 33)

**Prüfbericht 366-0531-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000827**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23

Stand: 27.03.2015



Seite: 2 von 2

commercial type: **RENAULT MEGANE SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA	e2*98/14*0068*..	47 -85	185/65R15		1); 2); 33)
		59 -102	205/55R15		
		102 -103	195/60R15		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0531-15-WIRD/N2**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.10**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
 Stand: 19.01.2016



Seite: 1 von 2

**Manufacturer : RENAULT**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 43  
 Hole circle (mm)/number of holes : 100/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1611	R1-1611	Without	60		520	1895	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
R	e2*2001/116*0327*..	48 -102	185/60R15 88 M+S		*); only CLIO; 1); 2); 33)	
			185/60R15 88H			
		100 -102	185/65R15-88V			
R	e2*2007/46*0008*..	48 -74	185/60R15 84 M+S		1); 2); 33)	
			185/60R15 84H			
		50 -78	185/60R15 88 M+S			
			63 -78	185/60R15 88H		

commercial type: **CLIO, CAPTUR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R	e2*2001/116*0327*..	48 -102	185/60R15		*); Grandtour; 1); 2); 33)
			185/60R15 M+S		
R	e2*2001/116*0327*..	55 -65	185/60R15 84H		*); only CLIO; station wagonlimousine; Hatchback; not Captur; 1); 2); 33)
		55 -94	185/60R15 M+S		
			185/60R15 88H		
	65	185/60R15 88			

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:  
 - the standard wheel size and offset.  
 - tyre size with service description (load and speed index) and tyre brand commitments

**Prüfbericht 366-0531-15-WIRD/N2**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.10**  
Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
Stand: 19.01.2016



Seite: 2 von 2

- as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.