

**Prüfbericht 366-0531-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.4**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
 Stand: 17.09.2015



Seite: 1 von 2

**Manufacturer : RENAULT**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 50  
 Hole circle (mm)/number of holes : 100/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1580	R1-1580	Without	60		500	1857	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : P

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : R

Tightening torque for fixing parts : 110 Nm

commercial type: **CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R	e2*2001/116*0327*..	48 -82	185/60R15 88H		1); 2); 33)
		48 -94	175/65R15 88		
			185/60R15 84		
			M+S		
		63 -82	185/60R15 84H		
		63 -82	185/60R15 88		
			M+S		

commercial type: **MODUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P	e2*2001/116*0319*..	48 -58	185/60R15 88		1); 2); 33)
		48 -82	175/65R15 88		
			185/60R15 84H		
		63 -82	185/60R15 88H		

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0531-15-WIRD/N1  
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.4**  
Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
Stand: 17.09.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.