

**Prüfbericht 366-0543-15-WIRD
zur Erteilung der ECE (E1) 124R- 000829**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15654108-27

Stand: 07.10.2015



Seite: 1 von 2

Manufacturer : CITROEN, PEUGEOT**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 15 H2 Off set(mm) : 27

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1700	R1-1700	Without	65		550	1973	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **C4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
N*5FL	e24*2007/46*0027*..	88	195/65R15-89H		1); 2); 33)

commercial type: **C4, DS4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
N	e2*2007/46*0040*..	68-88	195/65R15 91H 195/65R15-89H		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **308**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
4	e2*2001/116*0362*..	82	195/65R15 91H		*) ; SW/BREAK; 1); 2); 33)
4*****	e2*2001/116*0362*..	82	195/65R15 91H		*) ; Cabrio; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments

**Prüfbericht 366-0543-15-WIRD
zur Erteilung der ECE (E1) 124R- 000829**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15654108-27

Stand: 07.10.2015



Seite: 2 von 2

- as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0543-15-WIRD
zur Erteilung der ECE (E1) 124R- 000829**

ANLAGE: 9.2
Hersteller: MW Aftermarket Srl

Radtyp: 15654108-27
Stand: 07.10.2015



Seite: 1 von 2

Manufacturer : CITROEN, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 1/2 J X 15 H2 Off set(mm) : 27
Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1735	R1-1735	Without	65		650	1998	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 7*****, B9; 7

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 7*****, 7

Tightening torque for fixing parts : 90 Nm

commercial type: **BERLINGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B9	N129	55 -66	195/65R15 91 195/70R15C 98		1); 2); 33)
7 7*****	e2*2001/116*0366*.. e2*2001/116*0366*..	55 -88	195/65R15 91 195/70R15C 98 205/65R15-94H		1); 2); 33)
7	e2*2007/46*0002*..	55 -88	195/65R15 91 195/70R15C 98 205/65R15-94H		1); 2); 33)
7	e2*2007/46*0002*..	35	195/70R15C		*) ; Berlingo Electrique; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 7; B9; 7*****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 7*****, 7

Tightening torque for fixing parts : 90 Nm

Prüfbericht 366-0543-15-WIRD
zur Erteilung der ECE (E1) 124R- 000829

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15654108-27

Stand: 07.10.2015



Seite: 2 von 2

commercial type: **PARTNER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B9	N128	55 -66	195/65R15 91 195/70R15C 98		1); 2); 33)

commercial type: **PARTNER / RANCH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7	e2*2001/116*0365*..	55 -80	195/70R15C		1); 2); 33)
7****	e2*2001/116*0365*..	55 -88	195/65R15 91		
			195/70R15-98		
			205/65R15-94H		
7	e2*2007/46*0001*..	55 -88	195/65R15 91 195/70R15C 98 205/65R15-94H		1); 2); 33)
		66	195/65R15		
7	e2*2007/46*0001*..	35	195/70R15C		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.