

**Prüfbericht 366-0560-15-WIRD
zur Erteilung der ECE (E1) 124R- 000830**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 29.10.2015



Seite: 1 von 2

Manufacturer : CITROEN**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 26

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1589	R1-1589	Without	65		600	1960	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : R*6FZ*; L*****; R*4HT*; R*4HP*; R*4HR*; R*9HY*;
R*RHR*; R*6FY*; R*4HS*; R*4HX*; R*XFU*; R*9HZ*; R*RHL*;
R*RFJ*

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : L

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN C4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
L	e2*2001/116*0302*..	65 - 130	205/55R16 90V		1); 2); 33)
			205/55R16 91V		
			205/55R16 94V		
			80 - 103		
L*****	e2*2001/116*0302*..	65 - 130	205/55R16 90V		1); 2); 33)
			205/55R16 91V		
			205/55R16 94V		
			80 - 103		

commercial type: **CITROEN C5**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R*RFJ*	e2*2001/116*0304*..	103	215/55R16 93W		1); 2); 33)
R*RHL*	e2*2001/116*0315*..	93	215/55R16 93W		1); 2); 33)
R*RHR*	e2*2001/116*0306*..	100	215/55R16 93W		1); 2); 33)
R*XFU*	e2*2001/116*0308*..	152	215/55R16 93W		1); 2); 33)
R*4HP*	e2*2001/116*0348*..	120	215/55R16 93W		1); 2); 33)
			215/55R16 97W		
R*4HR*	e2*2001/116*0354*..	120	215/55R16 93W		1); 2); 33)
			215/55R16 97W		
R*4HS*	e2*2001/116*0353*..	125	215/55R16 93W		1); 2); 33)
			215/55R16 97W		
R*4HT*	e2*2001/116*0347*..	125	215/55R16 93W		1); 2); 33)
			215/55R16 97W		

Prüfbericht 366-0560-15-WIRD
zur Erteilung der ECE (E1) 124R- 000830

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 29.10.2015



Seite: 2 von 2

commercial type: **CITROEN C5**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R*4HX*	e2*2001/116*0307*..	98	215/55R16 93W		1); 2); 33)
R*6FY*	e2*2001/116*0334*..	92	215/55R16 93W		1); 2); 33)
R*6FZ*	e2*2001/116*0303*..	85	215/55R16 93W		1); 2); 33)
R*9HY*	e2*2001/116*0335*..	80	215/55R16 93W		1); 2); 33)
R*9HZ*	e2*2001/116*0305*..	80	215/55R16 93W		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0560-15-WIRD
zur Erteilung der ECE (E1) 124R- 000830**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 29.10.2015



Seite: 1 von 2

Manufacturer : **CITROEN, PEUGEOT**

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 26

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1663	R1-1663	Without	65		615	1961	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 7; 7*****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : U*****

Tightening torque for fixing parts : 90 Nm

commercial type: **BERLINGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7	e2*2001/116*0366*..	55 -88	215/55R16 93V		1); 2); 33)
7*****	e2*2001/116*0366*..				
7	e2*2007/46*0002*..	55 -88	215/55R16 93 M+S		*) ; 5-door;
			215/55R16 93V		1); 2); 33)

commercial type: **CITROEN C4 PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
U*****	e2*2001/116*0345*..	80 -120	215/55R16 93V		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **PARTNER / RANCH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7	e2*2001/116*0365*..	55 -88	215/55R16 93V		1); 2); 33)
7*****	e2*2001/116*0365*..				
7	e2*2007/46*0001*..	55 -88	215/55R16 93H		*) ; 5-door;
			215/55R16 93V		1); 2); 33)

**Prüfbericht 366-0560-15-WIRD
zur Erteilung der ECE (E1) 124R- 000830**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 29.10.2015



Seite: 2 von 2

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.