

**Prüfbericht 366-0560-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000830**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 29.10.2015



Seite: 1 von 2

**Manufacturer : PEUGEOT****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 31  
Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1582	R1-1582	Without	65		553	1930	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,  
for Type : 3\*RHS\*; 3\*RHY\*; 3\*RFN\*; 3\*RFK\*; 3\*9HZ\*; 3\*8HZ\*;  
3\*NFU\*; 3\*RHR\*

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type :  
3\*9HX\*; 3\*NFU\*; 3\*9HV\*; 3\*RFJ\*; 3\*9HY\*

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT 307**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
3*NFU*	e2*2001/116*0243*..	80	205/55R16 91V		1); 2); 33)
3*NFU*	e2*98/14*0243*..	80	205/55R16 91V		1); 2); 33)
3*RFJ*	e2*2001/116*0313*..	103	205/55R16 91V		1); 2); 33)
3*RFK*	e2*2001/116*0290*..	130	205/55R16 91V		1); 2); 33)
3*RFN*	e2*98/14*0244*..	100	205/55R16 91V		1); 2); 33)
3*RHR*	e2*2001/116*0235*..	100	205/55R16 91V		1); 2); 33)
3*RHS*	e2*98/14*0252*..	79	205/55R16		1); 2); 33)
3*RHY*	e2*98/14*0245*..	66	205/55R16		1); 2); 33)
3*8HZ*	e2*98/14*0251*..	50	205/55R16		1); 2); 33)
3*9HV*	e2*2001/116*0333*..	66	205/55R16 91V		1); 2); 33)
3*9HX*	e2*2001/116*0301*..	66	205/55R16 91V		1); 2); 33)
3*9HY*	e2*2001/116*0299*..	80	205/55R16 91V		1); 2); 33)
3*9HZ*	e2*2001/116*0287*..	80	205/55R16 91V		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0560-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000830**

**ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 29.10.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.