

Prüfbericht 366-0532-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000831

ANLAGE: 9.7
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 30.09.2015



Seite: 1 von 2

Manufacturer : CITROEN, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 23
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1651	R1-1651	Without	65		500	1894	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : S****, SH****, S; SH

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : D; SH; S*8FN; SH8FN; SH****

Tightening torque for fixing parts : 100 Nm

commercial type: **C-ELYSEE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
D	e2*2007/46*0225*..	53 -85	185/65R15 80		1); 2); 33)

commercial type: **C3, DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S****	e2*2007/46*0003*..	44 -88	185/65R15 88		*) ; 3-door; 5-door; 1); 2); 33)

commercial type: **C3, DS3, DS3 CABRIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S	e2*2007/46*0003*..	44 -88	185/65R15 81		1); 2); 33)
			185/65R15 88		
			185/65R15-88H		

commercial type: **C3 PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SH	e2*2001/116*0371*..	66 -70	195/60R15 88		1); 2); 33)
SH****	e2*2001/116*0371*..				
SH8FN	e24*2007/46*0029*..	67 -70	195/60R15 88		1); 2); 33)

commercial type: **DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S*8FN	e24*2007/46*0028*..	44 -88	185/65HR15		1); 2); 33)

Prüfbericht 366-0532-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000831

ANLAGE: 9.7
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 30.09.2015



Seite: 2 von 2

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
 for Type : W*****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
 for Type : D; C

Tightening torque for fixing parts : 90 Nm for Type : W*****
 100 Nm for Type : C; D

commercial type: **PEUGEOT 207**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
W*****	e2*2001/116*0340*..	50 -70	185/65R15 88		*); not Escapade (Ausf. WU****); 1); 2); 33)
		50 -88	185/65R15-88H		
W*****	e2*2001/116*0340*..	50 -70	185/65R15 88		*); not Escapade (Ausf. WU****); not convertible; Front wheel drive; not with increased chassis clearance; 1); 2); 33)
		50 -88	185/65R15-88H		

commercial type: **208, 2008**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C	e2*2007/46*0070*..	50 -88	185/65R15 81		1); 2); 33)

commercial type: **301**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
D	e2*2007/46*0224*..	53 -85	185/65R15 80		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.