

**Prüfbericht 366-0532-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000831**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 23.06.2015



Seite: 1 von 3

**Manufacturer : CITROEN, PEUGEOT**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 27  
Hole circle (mm)/number of holes : 108/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1372	R1-1372	Without	65		553	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : CITROEN**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN C2**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
J*KFU*	e2*2001/116*0344*..	65	185/55R15-82H		1); 2); 3)
J*KFV*	e2*2001/116*0284*..	54	185/55R15-82H		1); 2); 3)
J*NFU*	e2*2001/116*0285*..	80	185/55R15-82H		1); 2); 3)
J*8HX*	e2*2001/116*0286*..	50	185/55R15-82H		1); 2); 3)
J*8HZ*	e2*2001/116*0316*..	50	185/55R15-82H		1); 2); 3)

commercial type: **CITROEN C3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F*HFX*	e2*98/14*0256*..	44	185/60R15 84H		1); 2); 3)
F*KFU*	e2*2001/116*0289*..	65	185/60R15 84H		1); 2); 3)
F*KFV*	e2*98/14*0257*..	54	185/60R15 84H		1); 2); 3)
F*NFU*	e2*98/14*0258*..	80	185/60R15 84H		1); 2); 3)
F*8HX*	e2*98/14*0259*..	50	185/60R15 84H		1); 2); 3)
F*8HY*	e2*98/14*0261*..	66	185/60R15 84H		1); 2); 3)
F*8HZ*	e2*2001/116*0317*..	50	185/60R15 84H		1); 2); 3)
F*9HX*	e2*2001/116*0318*..	66	185/60R15 84H		1); 2); 3)
F*9HZ*	e2*2001/116*0329*..	80	185/60R15 84H		1); 2); 3)

commercial type: **CITROEN C3 PLURIEL**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
H	e2*2001/116*0266*..	50 -80	185/65R15-88H		1); 2); 3)

commercial type: **CITROEN C4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
L	e2*2001/116*0302*..	65 -103	195/65R15 91H		1); 2); 3)
L*****	e2*2001/116*0302*..	65 -103	195/65R15 91H		1); 2); 3)

**Prüfbericht 366-0532-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000831**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 23.06.2015



Seite: 2 von 3

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT 1007**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
K*****	e2*2001/116*0300*..	50 -80	185/60R15 84H		1); 2); 3)

commercial type: **PEUGEOT 206**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2*KFU*	e2*2001/116*0291*..	65	195/55R15 85H		1); 2); 3)
2*NFU*	e2*98/14*0238*..	80	185/55R15-82V 195/55R15 85H		1); 2); 3)
2*RFK*	e2*2001/116*0269*..	130	195/55R15 82V		1); 2); 3)
2*RFN*	e2*98/14*0239*..	100	185/55R15-82V 195/55R15 85H		1); 2); 3)
2*RFN*	e2*98/14*0239*..	100	195/55R15		*) ; Station wagon; 1); 2); 3)
2*RHY	e2*98/14*0174*..	66	185/55R15 195/55R15		*) ; Limousine; 1); 2); 3)
2*RHY	e2*98/14*0174*..	66	195/55R15		*) ; Station wagon; 1); 2); 3)
2*9HY*	e2*2001/116*0343*..	80	195/55R15 85H		1); 2); 3)
2*9HZ*	e2*2001/116*0310*..	80	195/55R15 85H		1); 2); 3)

commercial type: **PEUGEOT 206+**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2	e2*2001/116*0374*..	50 -55	185/60R15 84H		1); 2); 3)
2*****	e2*2001/116*0374*..				

commercial type: **PEUGEOT 307**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
3*KFU*	e2*2001/116*0288*..	65	195/65R15 91 195/65R15 91H		1); 2); 3)
3*KFU*	e2*2001/116*0288*..	65	195/65R15 91 195/65R15 91H		1); 2); 3)
3*KFW*	e2*98/14*0242*..	55	195/65R15		1); 2); 3)
3*NFU*	e2*2001/116*0243*..	80	195/65R15 91 195/65R15 91H		1); 2); 3)
3*NFU*	e2*98/14*0243*..	80	195/65R15 91		1); 2); 3)
3*RHY*	e2*98/14*0245*..	66	195/65R15		1); 2); 3)
3*8HZ*	e2*98/14*0251*..	50	195/65R15		1); 2); 3)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Prüfbericht 366-0532-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000831**

**ANLAGE: 9.3**

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 23.06.2015



Seite: 3 von 3

---

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 3) Only for vehicles from date of manufacture 04.2000.