

**Prüfbericht 366-0532-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000831**

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 23.06.2015



Seite: 1 von 1

**Manufacturer** : FORD**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 47,5

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1730	R1-1730	Without	63,35		425	1876	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : JA8; JA8-LPG

Accessories : Serie

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : JA8

Tightening torque for fixing parts : 100 Nm

commercial type: **FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA8	e9*2001/116*0069*..	44 -60	195/60R15		*); ; 1); 2); 33)
		44 -103	195/50R15		
			195/55R15		
		71	195/60R15		
JA8	e9*2001/116*0069*..	44 -88	195/50R15 82		1); 2); 33)
			195/60R15 88		
			195/60R15-88V		
			88	195/60R15-88H	
JA8-LPG	e13*2007/46*1058*..	68 -71	195/50R15 82		1); 2); 33)
			195/60R15 88		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.