

**Prüfbericht 366-0552-15-WIRD
zur Erteilung der ECE (E1) 124R- 000832**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16604108-30

Stand: 06.08.2015



Seite: 1 von 2

Manufacturer : CITROEN, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 23

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1781	R1-1781	Without	65		500	1894	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : Flachbund lose, Flachschauben M12x1,25

Tightening torque for fixing parts : 100 Nm

commercial type: **C3, DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S*****	e2*2007/46*0003*..	50-115	195/55R16		*) Citroen DS3; 3-türig; 1); 2); 33)
S*****	e2*2007/46*0003*..	44-88	195/55R16		*) Citroen C3; 5-türig; 1); 2); 33)
S*****	e2*2007/46*0003*..	44-115	195/55R16		*) 3-türig; 5-türig; 1); 2); 33)

commercial type: **C3, DS3, DS3 CABRIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S	e2*2007/46*0003*..	50-115	195/55R16		*) Citroen DS3; 3-türig; 1); 2); 33)
S	e2*2007/46*0003*..	44-88	195/55R16		*) Citroen C3; 5-türig; 1); 2); 33)
S	e2*2007/46*0003*..	60-115	195/55R16 81		*) Cabrio; 1); 2); 33)
S	e2*2007/46*0003*..	44-88	195/55R16 87		1); 2); 33)
		44-110	195/55R16 81		
		50-115	195/55R16 82V		

commercial type: **C3 PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SH	e2*2001/116*0371*..	66-88	195/55R16 91		1); 2); 33)
SH****	e2*2001/116*0371*..				
SH8FN	e24*2007/46*0029*..	67-70	195/55R16 91		1); 2); 33)

**Prüfbericht 366-0552-15-WIRD
zur Erteilung der ECE (E1) 124R- 000832**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16604108-30

Stand: 06.08.2015



Seite: 2 von 2

commercial type: **DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S*8FN	e24*2007/46*0028*..	67 -70	195/55R16 87T		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : Flachbund lose, Flachsrauben M12x1,25

Tightening torque for fixing parts : 100 Nm

commercial type: **208, 2008**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C	e2*2007/46*0070*..	50 -88	195/55R16 81		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0552-15-WIRD
zur Erteilung der ECE (E1) 124R- 000832**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16604108-30

Stand: 06.08.2015



Seite: 1 von 2

Manufacturer : **CITROEN****Wheel dates:**

Wheel size according to standard : 6 J X 16 H2

Off set(mm) : 23

Hole circle (mm)/number of holes : 108/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1747	R1-1747	Without	65		528	1894	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : SH; SH****; S*****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : S; SH

Tightening torque for fixing parts : 100 Nm

commercial type: **C3, DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S*****	e2*2007/46*0003*..	44 - 115	195/55R16		*) ; 3-türig; 5-türig; 1); 2); 33)

commercial type: **C3, DS3, DS3 CABRIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S	e2*2007/46*0003*..	44 - 88	195/55R16 87		1); 2); 33)
		44 - 110	195/55R16 81		
		50 - 115	195/55R16 82V		

commercial type: **C3 PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SH	e2*2007/46*0110*..	66 - 88	195/55R16 84		1); 2); 33)
SH****	e2*2001/116*0371*..	66 - 88	195/55R16 91		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.

**Prüfbericht 366-0552-15-WIRD
zur Erteilung der ECE (E1) 124R- 000832**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16604108-30

Stand: 06.08.2015



Seite: 2 von 2

- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.