

**Prüfbericht 366-0534-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000837**

**ANLAGE: 9.1**  
Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
Stand: 29.07.2015



Seite: 1 von 3

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 38  
Hole circle (mm)/number of holes : 100/5      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1229	R1-1229	Without	57		515	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8L	e1*95/54*0042*.., e1*98/14*0042*..	66 - 110	185/65R15		1); 2); 33)
			195/65R15		
		66 - 132	205/60R15		
		132	195/65R15		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SEAT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 120 Nm

commercial type: **SEAT TOLEDO/LEON**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1M	e9*97/27*0026*..	55 - 92	195/65R15		1); 2); 33)
1M	e9*98/14*0026*..	50 - 110	195/65R15		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SKODA**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm

**Prüfbericht 366-0534-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000837**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41

Stand: 29.07.2015



Seite: 2 von 3

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1U	e11*2001/116*0066*..	55	195/65R15 91		1); 2); 33)
		74 -75	195/65R15 91H		
		110	195/65R15-91V		
1U	e11*2007/46*0011*..	55	195/65R15 91		1); 2); 33)
		74 -75	195/65R15 91H		
		110	195/65R15-91V		
1U	e11*95/54*0066*..	44 -110	195/65R15		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 9C; 9C

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 1Y; 1J; 9N; 9C

Tightening torque for fixing parts : 110 Nm for Type : 9C  
120 Nm for Type : 1J; 1Y; 9C; 9N

commercial type: **GOLF / BORA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1J	e1*2001/116*0071*..	50 -66	195/65R15 91		1); 2); 33)
		74 -85	195/65R15 91H		
		96 -110	195/65R15-91V		
1J	e1*96/79*0071*..	50 -110	195/65R15		1); 2); 33)
1J	e1*98/14*0071*..	50 -110	195/65R15		1); 2); 33)

commercial type: **NEW BEETLE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9C	e1*2001/116*0106*..	55 -75	195/65R15 91		1); 2); 33)
		77 -85	195/65R15 91H		
		110	195/65R15-91V		
9C	e1*97/27*0106*..	66 -85	195/65R15		1); 2); 33)
9C	e1*98/14*0106*..	55 -110	195/65R15		1); 2); 33)

commercial type: **NEW BEETLE CABRIOLET**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1Y	e1*2001/116*0205*..	55 -75	195/65R15 91		*); Cabrio; 1); 2); 33)
		77 -85	195/65R15 91H		
		110	195/65R15-91V		

commercial type: **VW POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9N	e1*2001/116*0174*..	40 -77	185/60R15 84		*); Polo-Fun; Polo-Cross; 1); 2); 33)

**Prüfbericht 366-0534-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000837**

**ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41

Stand: 29.07.2015



Seite: 3 von 3

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0534-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.3**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
 Stand: 04.11.2015



Seite: 1 von 3

**Manufacturer : SEAT, SKODA, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 38  
 Hole circle (mm)/number of holes : 100/5      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1727	R1-1727	Without	57		480	1884	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SEAT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm

commercial type: **IBIZA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6J	e9*2001/116*0067*..	44 -77	185/60R15 84		*); from e9*2001/116*0067*21; 1); 2); 33)
		77	175/65R15 84		
		105 -132	185/60R15 88		
6J	e9*2001/116*0067*..	44 -77	185/60R15 84		*); only to e9*2001/116*0067*20; 1); 2); 33)
			185/60R15 84 M+S		
		51 -77	185/60R15 84H		
		51 -110	185/60R15 88 M+S		
		55 -77	175/65R15 84		
		55 -110	185/60R15 88		
		66 -77	175/65R15 84H		

commercial type: **TOLEDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0251*..	55 -90	185/60R15 84		*); from e11*2007/46*0251*01; Limousine; Front wheel drive; 1); 2); 33)
		66 -90	195/55R15		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SKODA**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm

**Prüfbericht 366-0534-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.3**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
 Stand: 04.11.2015



Seite: 2 von 3

commercial type: **RAPID**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0250*..	55-90	185/60R15 84		*); RAPID SPACEBACK; from NT*06; Front wheel drive; 1); 2); 33)
		66-90	195/55R15 85H		
NH	e11*2007/46*0250*..	55-92	185/60R15		*); from e11*2007/46*0250*01; Front wheel drive; 1); 2); 33)
		66-90	195/55R15		
		66-92	185/60R15 M+S		

commercial type: **ROOMSTER, FABIA, PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	e11*2001/116*0291*..	44-81	185/60R15		*); from e11*2001/116*0291*26; 1); 2); 33)
5J	e11*2007/46*0013*..	44-81	185/60R15		1); 2); 33)
5J	e11*2007/46*0013*..	77	195/55R15 85H		*); Fabia station wagon; Scout; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 6R

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 6R; 9N

Tightening torque for fixing parts : 120 Nm

commercial type: **POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6R	e1*2001/116*0510*..	44-103	185/60R15		1); 2); 33)
		55-132	185/60R15 M+S		
		77-103	175/65R15		
6R	e1*2001/116*0510*..	44-77	185/60R15		*); POLO; 1); 2); 33)
6R	e1*2007/46*0486*..	44-77	185/60R15 84		1); 2); 33)
		77	185/60R15 84H		

commercial type: **VW POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9N	e1*2001/116*0174*..	40-77	185/60R15 84		*); Polo-Fun; Polo- Cross; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Prüfbericht 366-0534-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.3**  
Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
Stand: 04.11.2015



Seite: 3 von 3

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.