

**Prüfbericht 366-0562-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840**

**ANLAGE: 9.8**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45  
 Stand: 26.07.2016



Seite: 1 von 2

**Manufacturer : PEUGEOT**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 44  
 Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1476	R1-1476	Without	65,1		580	2025	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 6\*6FZ\*; 6\*RFJ\*; 6\*RHL\*; 6\*9HZ\*; 6\*6FY\*; 6\*9HY\*; 6\*RFN\*

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 6\*\*\*\*\*; 6\*RHR\*

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT 407**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6*****	e2*2001/116*0369*..	100 -103	205/60R16 92V		*); Station wagon; Limousine; 1); 2); 33)
		100 -120	205/60R16 92H		
6*RFJ*	e2*2001/116*0331*..	103	205/60R16 92V		1); 2); 33)
6*RFN*	e2*2001/116*0293*..	100	205/60R16 92V		1); 2); 33)
6*RHL*	e2*2001/116*0312*..	93	205/60R16 92H		1); 2); 33)
6*RHR*	e2*2001/116*0297*..	100	205/60R16 92H		1); 2); 33)
			205/60R16 92V		
6*6FY*	e2*2001/116*0330*..	92	205/60R16 92H		1); 2); 33)
			205/60R16 92V		
6*6FZ*	e2*2001/116*0292*..	85	205/60R16 92H		1); 2); 33)
			205/60R16 92V		
6*9HY*	e2*2001/116*0336*..	80	205/60R16 92H		1); 2); 33)
			205/60R16 92V		
6*9HZ*	e2*2001/116*0296*..	80	205/60R16 92H		1); 2); 33)
			205/60R16 92V		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:  
 - the standard wheel size and offset.  
 - tyre size with service description (load and speed index) and tyre brand commitments

**Prüfbericht 366-0562-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840**

**ANLAGE: 9.8**  
Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45  
Stand: 26.07.2016



---

Seite: 2 von 2

- as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.