

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 1 von 2

**Manufacturer** : FORD**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50

Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1645	R1-1645	Without	63,35		703	2025	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : FORD

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad, for Type : WA6

Accessories : Serie

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad, for Type : WA6

Tightening torque for fixing parts : 133 Nm

commercial type: **GALAXY, S-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
WA6	e13*2001/116*0185*..	74-92	215/60R16 95		1); 2); 33)
		92-96	215/60R16 94		
		96-103	215/60R16 93H		
		103	215/60R16 94H		
		107	215/60R16 92H		
		107-118	215/60R16 95H		
		129	215/60R16 95V		
		162	215/60R16 94W		
WA6	e13*2001/116*0185*..	74-103	215/60R16 95		1); 2); 33)
		74-118	215/60R16 95H		
		85	215/60R16 99		
		85-176	215/60R16 95V		
		146-149	215/60R16 99		
		162-176	215/60R16 95W		
WA6	e13*2001/116*0185*..	74-149	215/60R16		*) ; Ford Galaxy; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
- the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

**ANLAGE: 9.3**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



---

Seite: 2 von 2

- as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 1 von 3

**Manufacturer : FORD****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50

Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1707	R1-1707	Without	63,35		650	1958	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : FORD**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : DB3; DA3-LPG; BA7-LPG; DA3-CNG; DM2-LPG; DA3; DM2; BA7; DM2-CNG

Accessories : Serie

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : DXA; DXA-LPG; BA7; DM2; DYB

Tightening torque for fixing parts : 120 Nm for Type : DA3; DB3  
120 Nm ( C-max 120Nm, Kuga 130Nm ) Nm for Type : DM2  
120 Nm ( Nur C-MAX ) Nm for Type : DM2; DM2-CNG; DM2-LPG  
130 Nm for Type : DA3-CNG; DA3-LPG; DXA; DXA-LPG; DYB  
130 Nm ( Nur Kuga ab Modeljahr 2013 ) Nm for Type : DM2  
130 Nm ( Nur Kuga bis Modeljahr 2012 ) Nm for Type : DM2  
140 Nm for Type : BA7; BA7-LPG

commercial type: **FOCUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DA3	e13*2001/116*0144*..	59 -107	205/55R16		*); from e13*2001/116*0144*12; 1); 2); 33)
		81 -166	205/55R16 91 M+S		
		92 -107	205/55R16 91H		
		100 -107	205/55R16 91V		
DA3-CNG	e13*2001/116*1017*..	91 -107	205/55R16 M+S		1); 2); 33)
			205/55R16 86V		
DA3-LPG	e13*2001/116*0999*..	103 -107	205/55R16 86V		1); 2); 33)
			205/55R16-88V		

**Prüfbericht 366-0562-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000840**

**ANLAGE: 9.4**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45  
 Stand: 21.07.2015



Seite: 2 von 3

commercial type: **FOCUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DB3	e13*2001/116*0157*..	59 -74	205/55R16 84		*); from e13*2001/116*0157*09; Cabrio; Stufenheck; 1); 2); 33)
		66 -80	205/55R16-86		
		74 -81	205/55R16-88		
		74 -107	205/55R16 M+S		
		85	205/55R16 84H		
			205/55R16-88H		
		92 -107	205/55R16 85V		
		100	205/55R16 90V		
			205/55R16-88V		
		107	205/55R16-85		
205/55R16-86H					
205/55R16-89V					
DB3	e13*2001/116*0157*..	59 -74	205/55R16 84		*); only to e13*2001/116*0157*08; Stufenheck; 1); 2); 33)
		66 -80	205/55R16-85		
		80	205/55R16-86		
		85	205/55R16 84H		
			205/55R16-86H		
		85 -107	205/55R16 M+S		
		92	205/55R16 84V		
		98 -100	205/55R16 87V		
		107	205/55R16 85V		
		DYB	e13*2007/46*1138*..	63 -125	
215/55R16 93H					
110 -134	205/55R16 91V				
	215/55R16 93V				

commercial type: **FORD C-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2-CNG	e13*2001/116*1018*..	91 -107	205/55R16 87		1); 2); 33)
			M+S		
			205/55R16 87V		
DM2-LPG	e13*2001/116*1000*..	103 -107	205/55R16 87V		1); 2); 33)

commercial type: **FORD C-MAX / KUGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	66 -107	205/55R16 91		*); C-MAX only; 1); 2); 33)
		81 -107	205/55R16 M+S		
DM2	e13*2001/116*0109*..	66 -107	205/55R16 91	C-MAX only	*); Kuga only; 1); 2); 33)
			81 -107	205/55R16 M+S	
		100	235/60R16 100	Only Kuga to Modeljahr 2012	
DM2	e13*2001/116*0109*..	85 -134	215/65R16 98V		*); Only Kuga from Modyear 2013; from e13*2001/116*0109*31; 1); 2); 33)
			235/60R16-100V		
		147	235/60R16		

**Prüfbericht 366-0562-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 3 von 3

commercial type: **FORD C-MAX / KUGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	100 -120	235/60R16 100		*); Only Kuga to Modeljahr 2012; all-wheel drive; Front wheel drive; 1); 2); 33)
		147	235/60R16 91V		

commercial type: **FORD MONDEO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
BA7	e13*2001/116*0249*..	85 -177	215/60R16		*); up to e13*2001/116*0249*26; 1); 2); 33)	
			215/60R16 M+S			
BA7	e13*2001/116*0249*..	74 -88	205/55R16		*); up to e13*2001/116*0249*25; 1); 2); 33)	
			74 -103	215/55R16 93H		
			74 -162	215/55R16 M+S		
			81 -92	205/55R16 M+S		
			107 -120	215/55R16 93V		
			149 -176	215/55R16 93W		
BA7-LPG	e13*2001/116*1015*..	104 -107	215/55R16 M+S		1); 2); 33)	
			215/55R16 93V			

commercial type: **Grand C-MAX, C-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
DXA	e13*2007/46*1103*..	63 -134	205/55R16		*); Only C-MAX; MPV; Front wheel drive; 1); 2); 33)	
			215/55R16			
DXA	e13*2007/46*1103*..	63 -110	205/55R16 91H		1); 2); 33)	
			63 -120	215/55R16 93H		
			70 -134	215/55R16 93V		
			77 -92	205/55R16 94H		
				205/55R16 94V		
			134	205/55R16 91V		
DXA-LPG	e13*2007/46*1288*..	88	205/55R16 91H		1); 2); 33)	
			215/55R16 93H			

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.5

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 1 von 2

**Manufacturer : FORD****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50

Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1886	R1-1886	Without	63,35		678	1989	51/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : FORD**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm ( Nur C-MAX ) Nm for Type : DM2  
 130 Nm ( Nur Kuga ab Modeljahr 2013 ) Nm for Type : DM2  
 130 Nm ( Nur Kuga bis Modeljahr 2012 ) Nm for Type : DM2  
 135 Nm for Type : PJ2; PU2

commercial type: **FORD C-MAX / KUGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	66 -107	205/55R16 91		*); C-MAX only; 1); 2); 33)
		81 -107	205/55R16 M+S		
DM2	e13*2001/116*0109*..	85 -134	215/65R16 98V		*); Only Kuga from Modeyear 2013; from e13*2001/116*0109*31; 1); 2); 33)
		147	235/60R16-100V		
DM2	e13*2001/116*0109*..	100 -120	235/60R16 100		*); til modelyear 2012; until e13*2001/116*0109*31; all-wheel drive; Front wheel drive; 1); 2); 33)
		147	235/60R16 91V		

commercial type: **TOURNEO CONNECT,TRANSIT CONNECT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PJ2	e1*2001/116*0207*..	55 -125	205/60R16		1); 2); 33)
			205/60R16 M+S		
			215/55R16		
			215/55R16 M+S		

commercial type: **TRANSIT CONNECT,TOURNEO CONNECT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PU2	e1*2007/46*0272*..	55 -110	205/60R16		1); 2); 33)
			205/60R16 M+S		
			215/55R16		
			215/55R16 M+S		

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

**ANLAGE: 9.5**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



---

Seite: 2 von 2

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.