

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 1 von 2

**Manufacturer : FORD****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 52,5

Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1557	R1-1557	Without	63,35		610	1930	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : FORD**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 100 Nm for Type : BWY; B4Y; B5Y; DA3; DB3  
120 Nm for Type : DA3  
120 Nm ( Nur C-MAX ) Nm for Type : DM2

commercial type: **FOCUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DA3	e13*2001/116*0144*..	59 -107	205/55R16		1); 2); 33)
		85 -166	205/55R16 M+S		
DA3	e13*2001/116*0144*..	59 -107	205/55R16		1); 2); 33)
DB3	e13*2001/116*0157*..	59 -74	205/55R16 84		*); only to e13*2001/116*0157*08; Cabrio; Stufenheck; 1); 2); 33)
		66 -80	205/55R16-85		
		80	205/55R16-86		
		85	205/55R16 84H		
			205/55R16-86H		
		85 -107	205/55R16 M+S		
		92	205/55R16 84V		
		98 -100	205/55R16 87V		
107	205/55R16 85V				

commercial type: **FORD C-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	66 -107	205/55R16		*); Only C-MAX; 1); 2); 33)
		80 -107	205/55R16 M+S		
		100	205/55R16-88H		
		107	205/55R16 87V		

**Prüfbericht 366-0562-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 2 von 2

commercial type: **FORD MONDEO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BWY	e1*98/14*0156*..	66 -150	205/50R16		1); 2); 33)
			205/55R16		
		66 -166	205/55R16 89 M+S		
B4Y	e1*98/14*0154*..	66 -150	205/55R16		1); 2); 33)
		66 -166	205/55R16		
		85 -150	205/50R16		
B5Y	e1*98/14*0155*..	66 -150	205/50R16		1); 2); 33)
			205/55R16		
		66 -166	205/55R16		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

### Restrictions

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 1 von 2

**Manufacturer** : VOLVO**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 52,5

Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1577	R1-1577	Without	63,35		550	1989	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : VOLVO

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : M-2D; M

Accessories : Serie

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : M

Tightening torque for fixing parts : 90 Nm for Type : M-2D  
110 Nm for Type : Mcommercial type: **C30**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
M-2D	e1*2001/116*0427*..	74 - 162	195/60R16 205/55R16		1); 2); 33)

commercial type: **VOLVO S40, V50, C70, C30,V40**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
M	e4*2001/116*0076*..	74 - 169	195/60R16 205/55R16		1); 2); 33)
M	e4*2001/116*0076*..	84 - 187	205/55R16		*) ; VOLVO V40; VOLVO V40 CrossCountry; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0562-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000840**

**ANLAGE: 9.2**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 21.07.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.