

**Prüfbericht 366-0575-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000841**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705108-48

Stand: 29.07.2015



Seite: 1 von 2

**Manufacturer** : CITROEN, FIAT, PEUGEOT

**Wheel dates:**

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 42

Hole circle (mm)/number of holes : 108/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1675	R1-1675	Without	65		850	2025	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **CITROEN JUMPY**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
G9	L863	66-120	215/60R16C 103		*) ; Lkw geschl.Kasten (Serie); Front wheel drive; 1); 2); 33)

commercial type: **JUMPY,DISPATCH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
X	e2*2001/116*0350*..	66-120	215/60R16 99	5JK	*) ; Station wagon;
X*****	e2*2001/116*0350*..		215/60R16C		Front wheel drive; 1); 2); 33)
X	e2*2007/46*0045*..	66-120	215/60R16 99	5JK	1); 2); 33)
			215/60R16C		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **FIAT SCUDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
270	e2*2001/116*0351*..	66-103	215/60R16 99		*) ; Station wagon;
			215/60R16C		Front wheel drive; 1); 2); 33)

**Prüfbericht 366-0575-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000841**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705108-48

Stand: 29.07.2015



Seite: 2 von 2

commercial type: **FIAT SCUDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
270L	L862	66 -103	215/60R16C 103		*) ; Lkw geschl.Kasten (Serie); Front wheel drive; 1); 2); 33)

commercial type: **SCUDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
270	e2*2007/46*0056*..	66 -120	215/60R16 99 215/60R16C	5JK	*) ; Station wagon; Front wheel drive; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **EXPERT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
G9	L867	66 -120	215/60R16C 103		*) ; Lkw geschl.Kasten (Serie); Front wheel drive; 1); 2); 33)
X	e2*2007/46*0046*..	66 -120	215/60R16 99 215/60R16C	5JK	1); 2); 33)

commercial type: **PEUGEOT EXPERT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
X	e2*2001/116*0349*..	66 -120	215/60R16 99	5JK	*) ; Station wagon;
X*****	e2*2001/116*0349*..		215/60R16C		Front wheel drive; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

### Restrictions

5JK) This tire size is only permitted on vehicles with a maximum permissible axle load of 1550kg.

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.