

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842

ANLAGE: 9.2
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55
 Stand: 18.06.2015



Seite: 1 von 2

Manufacturer : SEAT, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 33
 Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1723	R1-1723	Without	57		730	2025	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **SEAT ALHAMBRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7N	e1*2007/46*0402*..	85	205/60R16 96		*); Front wheel drive; 1); 2); 33)
			215/60R16 95		
		100 - 130	205/60R16 96H		
			215/60R16 95H		
			147	205/60R16 96V	
215/60R16 95V					
7N	e1*2007/46*0435*..	85	205/60R16 96		*); Front wheel drive; 1); 2); 33)
			215/60R16 95		
		100 - 130	205/60R16 96H		
			215/60R16 95H		
			147	205/60R16 96V	
215/60R16 95V					

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **TIGUAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5N	e1*2001/116*0450*..	81	215/65R16 98		*); From e1*2001/116*0450*11; 1); 2); 33)
			90 - 132	215/65R16 98H	
		155	215/65R16 98V		
5N	e1*2001/116*0450*..	81 - 147	215/65R16 98H		*); Only to e1*2001/116*0450*10; all-wheel drive; 1); 2); 33)

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842

ANLAGE: 9.2
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55
 Stand: 18.06.2015



Seite: 2 von 2

commercial type: **TIGUAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5N	e1*2007/46*0487*..	81	215/65R16 98		*); From e1*2007/46*0487*02; 1); 2); 33)
		90 -132	215/65R16 98H		
		155	215/65R16 98V		
5N	e1*2007/46*0487*..	90 -147	215/65R16 98H		*); Only to e1*2007/46*0487*01; 1); 2); 33)

commercial type: **VW SHARAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7N	e1*2007/46*0401*..	85	205/60R16 96		*); all-wheel drive; Front wheel drive; 1); 2); 33)
			215/60R16 95		
		100 -130	205/60R16 96H		
			215/60R16 95H		
		147	205/60R16 96V		
215/60R16 95V					
7N	e1*2007/46*0434*..	85	205/60R16 96		*); Front wheel drive; 1); 2); 33)
			215/60R16 95		
		100 -130	205/60R16 96H		
			215/60R16 95H		
		147	205/60R16 96V		
215/60R16 95V					

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.