

**Prüfbericht 366-0563-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842**

**ANLAGE: 9.3**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55  
 Stand: 18.06.2015



Seite: 1 von 2

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 46  
 Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1852	R1-1852	Without	57		615	1927	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3, S3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8V	e1*2007/46*0607*..	77 -135	205/55R16 91 M+S		*); not S3; Hatchback; 1); 2); 33)
			205/55R16 91W		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SEAT**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **LEON / LEON SC / LEON ST / LEON X-PERIENCE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5F	e9*2007/46*0094*..	63 -135	205/55R16		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SKODA**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5E	e11*2007/46*0243*..	63	205/55R16 91		1); 2); 33)
		66 -81	205/55R16 91H		
		103 -135	205/55R16 91V		

**Prüfbericht 366-0563-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842**

**ANLAGE: 9.3**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55  
 Stand: 18.06.2015



Seite: 2 von 2

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AUV	e1*2007/46*0627*..	63	205/55R16 91		1); 2); 33)
		77 -110	205/55R16 91H		

commercial type: **GOLF, GOLF VARIANT, GOLF SPORTSVAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AU	e1*2007/46*0623*..	63 -85	205/55R16 91		1); 2); 33)
		77 -92	205/55R16 91H		
		92 -135	205/55R16 91V		
		162	205/55R16 M+S		
			205/55R16 91W		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

### Restrictions

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.