

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842

ANLAGE: 9.1
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55
 Stand: 18.06.2015



Seite: 1 von 5

Manufacturer : AUDI, QUATTRO GmbH, SEAT, SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50
 Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1491	R1-1491	Without	57		625	1930	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : AUDI

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : 8P

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : 8P

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3 CABRIOLET**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8P	e1*2001/116*0456*..	75	205/55R16 91H		1); 2); 33)
		75-147	205/55R16 91 M+S		
		77-118	205/55R16 91V		
		100-147	205/55R16 91W		

commercial type: **AUDI A3,S3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8P	e1*2001/116*0217*..	66-125	205/55R16 91V		*); Sportback (4-türig); AUDI A3;
		66-147	205/55R16 91 M+S		
		75-85	205/55R16 91H		1); 2); 33)
		77-147	205/55R16 91W		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : QUATTRO GmbH

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 120 Nm

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842

ANLAGE: 9.1
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55
 Stand: 18.06.2015



Seite: 2 von 5

commercial type: **AUDI S3,RS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8P	e1*2001/116*0241*..	110	205/55R16 91		1); 2); 33)
			M+S		
			205/55R16 91V		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 5P; 1P

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 5PN; 5P

Tightening torque for fixing parts : 120 Nm

commercial type: **ALTEA, ALTEA XL, FREETRACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
5PN	e9*2007/46*0012*..	63 -77	205/55R16 91		1); 2); 33)	
			92 -100			205/55R16 91H
			103 -147			205/55R16 91V
			205/60R16 91V			
5PN	e9*2007/46*0012*..	103 -155	205/55R16 91V		*); Altea Freetrack; 1); 2); 33)	
			205/60R16 91V			

commercial type: **ALTEA, ALTEA XL, TOLEDO, FREETRACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
5P	e9*2001/116*0050*..	77 -92	205/55R16 91		*); Altea Freetrack; Altea 4 Freetrack; 1); 2); 33)	
			103 -155			205/55R16 91
						M+S
						205/60R16 M+S
		125 -155	205/55R16 91V			
			205/60R16 91V			
5P	e9*2001/116*0050*..	63 -92	205/55R16 91		*); Altea; Altea XL; Toledo; 125/147kW from NT*13; 1); 2); 33)	
			63 -125			205/55R16 91V
			63 -147			205/55R16 91
						M+S
		92 -118	205/55R16 91H			

commercial type: **LEON**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
1P	e9*2001/116*0052*..	63 -125	205/55R16 91V		RC1; 1); 2); 33)	
			63 -147			205/55R16 94
						M+S
			63 -155			205/55R16 91
						M+S
		92 -100	205/55R16 91H			
		147 -155	205/55R16 91W			

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55

Stand: 18.06.2015



Seite: 3 von 5

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 1Z

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 1Z

Tightening torque for fixing parts : 120 Nm

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1Z	e11*2001/116*0230*..	59-90	205/55R16 91H		*); Only Octavia; only to e11*2001/116*0230*28; 1); 2); 33)
		81-118	205/55R16 91V		
1Z	e11*2001/116*0230*..	55-85	205/55R16 91H		*); Only Octavia; from e11*2001/116*0230*29; 1); 2); 33)
		100-118	205/55R16 91V		
1Z	e11*2007/46*0012*..	59-90	205/55R16 91H		1); 2); 33)
		81-118	205/55R16 91V		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 1KP; 1T

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 1KP; 1T; 1t; 16; 1K; 1KM

Tightening torque for fixing parts : 120 Nm

commercial type: **GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1K	e1*2001/116*0242*..	90-103	205/55R16 91H		*); Cabrio; 1); 2); 33)
		155	205/55R16 91W		
1K	e1*2001/116*0242*..	55-85	205/55R16 91H		*); Only Golf 5; only to e1*2001/116*0242*24; 1); 2); 33)
		90	205/55R16		
		100-125	205/55R16 91V		
		147	205/55R16 91W		
1K	e1*2001/116*0242*..	59-77	205/55R16 91		1); 2); 33)
		81-103	205/55R16 91H		
		118-125	205/55R16 91V		
		155	205/55R16 91V		
1K	e1*2007/46*0490*..	66-77	205/55R16 91		*); Only Golf 6; 1); 2); 33)
		90-103	205/55R16 91H		
		118	205/55R16 91V		

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842
ANLAGE: 9.1
 Hersteller: MW Aftermarket Srl

 Radtyp: 16655112-55
 Stand: 18.06.2015


Seite: 4 von 5

commercial type: **GOLF PLUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1KP	e1*2001/116*0304*..	77 -118	205/55R16 91		*) ; Only CrossGolf 6; From e1*2001/116*0304*14; 1); 2); 33)
1KP	e1*2001/116*0304*..	75 -118	205/55R16 91		*) ; Only CrossGolf 5; Only to e1*2001/116*0304*13; 1); 2); 33)
1KP	e1*2001/116*0304*..	59 -118	205/55R16 91		*) ; Only Golf Plus 6; From e1*2001/116*0304*14; 1); 2); 33)
1KP	e1*2001/116*0304*..	55 -125	205/55R16 91		*) ; Only Golf Plus 5; Only to e1*2001/116*0304*13; 1); 2); 33)
1KP	e1*2007/46*0491*..	77	205/55R16 91		*) ; Only Golf Plus 6; 1); 2); 33)
		77 -90	205/55R16 91H		

commercial type: **JETTA, BEETLE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
16	e1*2007/46*0539*..	77	205/55R16 91		*) ; Only Jetta (Stufenheck); 1); 2); 33)
		90 -110	205/55R16 91H		
		118 -147	205/55R16 91V		
		147 -155	205/55R16 91W		

commercial type: **JETTA, GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1KM	e1*2001/116*0328*..	59 -147	205/55R16 91 M+S		*) ; Golf 5 (Variant); only to e1*2001/116*0328*14; 1); 2); 33)
1KM	e1*2001/116*0328*..	66 -147	205/55R16 91 M+S		*) ; JETTA (Limousine); 1); 2); 33)
1KM	e1*2001/116*0328*..	59 -118	205/55R16 91		*) ; GOLF 6 (Variant); from e1*2001/116*0328*15; 1); 2); 33)
1KM	e1*2007/46*0492*..	63 -90	205/55R16		*) ; GOLF 6 (Variant); 1); 2); 33)

commercial type: **TOURAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1t	e1*2007/46*0506*..	66 -125	205/55R16		*) ; Touran; 1); 2); 33)
1T	e1*2001/116*0211*..	66 -125	205/55R16		*) ; Touran; 1); 2); 33)

Prüfbericht 366-0563-15-WIRD/N1**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842****ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55

Stand: 18.06.2015



Seite: 5 von 5

commercial type: **TOURAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1T	e1*2007/46*0357*..	66 -77	205/55R16 91		*); Touran; 1); 2); 33)
		77	205/55R16 94		
		100 -103	205/55R16 91H		
		103	205/55R16 94H		
		125	205/55R16 91V		
		125 -130	205/55R16 94V		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

RC1) The use of this wheel/tyre combination is not permissible on vehicle models with 136kW petrol engine.

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.