

**Prüfbericht 366-0577-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000845**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705112-59

Stand: 03.03.2016



Seite: 1 von 2

**Manufacturer : AUDI****Wheel dates:**

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 39

Hole circle (mm)/number of holes : 112/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1702	R1-1702	Without	66,5		638	1989	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : B81

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : B81; B8

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A5,S5,A4,S4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B8	e1*2001/116*0430*..	88	205/60R16 92		1); 2); 33)
		88-100	205/60R16 92V		
		88-105	205/60R16 92 M+S		
		88-125	205/60R16 92W		
		105-120	205/60R16 92 M+S		
		130	205/60R16 92 M+S		
B81	e13*2007/46*1084*..	88	205/60R16 92V		*); AUDI A4; 1); 2); 33)
		88-118	205/60R16 92W		
		120	205/60R16 92 M+S		
B81	e13*2007/46*1084*..	88-125	205/60R16 205/60R16 M+S		*); AUDI A4; all-wheel drive; Front wheel drive; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:  
- the standard wheel size and offset.

**Prüfbericht 366-0577-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000845**

**ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 16705112-59

Stand: 03.03.2016



Seite: 2 von 2

- tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.