

Prüfbericht 366-0566-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847

ANLAGE: 9.5
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62
 Stand: 17.06.2015



Seite: 1 von 1

Manufacturer : Nissan International S. A.

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 40
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1740	R1-1740	Without	66		608	2092	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : Nissan International S. A.

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 113 Nm

commercial type: **NISSAN QASHQAI, QASHQAI + 2**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
J10	e11*2001/116*0295*..	76-110	215/65R16 98		*) ; Nissan Qashqai short; Nissan Qashqai +2 (long); 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

Prüfbericht 366-0566-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62
 Stand: 17.06.2015



Seite: 1 von 1

Manufacturer : Nissan International S. A.

Wheel dates:

Wheel size according to standard : 6 1/2 JJ X 16 CH Off set(mm) : 40
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1834	R1-1834	Without	66		635	2300	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : Nissan International S. A.

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 108 Nm for Type : ZE0
 118 Nm for Type : F15

commercial type: **JUKE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F15	e11*2007/46*0132*..	69 - 160	205/60R16		*); all-wheel drive; Front wheel drive; 1); 2); 33)
		81	215/60R16		

commercial type: **NISSAN LEAF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
ZE0	e11*2007/46*0230*..	80	205/55R16		*); E-car 80kW; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.