

**Prüfbericht 366-0566-15-WIRD/N2**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

**ANLAGE: 9.7**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62  
 Stand: 03.11.2015



Seite: 1 von 1

**Manufacturer : TOYOTA**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16      Off set(mm) : 45  
 Hole circle (mm)/number of holes : 114,3/5      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1862	R1-1862	Without	60		575	1928	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : TOYOTA**

Mounting parts : conical collar nut M12x1,5  
 Tightening torque for fixing parts : 103 Nm for Type : E15J(a); HE15U(a)  
 110 Nm for Type : E15UT(a)

commercial type: **AURIS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E15J(a)	e11*2001/116*0299*..	66 -108	205/55R16 91V		1); 2); 33)
E15UT(a)	e11*2001/116*0305*..	66 -130	205/55R16 91V		1); 2); 33)
E15UT(a)	e11*2001/116*0305*..	66 -97	205/55R16 91V		*) ; AURIS TOURING SPORTS; from e11*2001/116*0305*15; 1); 2); 33)
E15UT(a)	e11*2001/116*0305*..	91 -97	205/55R16		*) ; from e11*2001/116*0305*14; 1); 2); 33)
HE15U(a)	e11*2007/46*0018*..	73	205/55R16 91V		1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.