

**Prüfbericht 366-0566-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

**ANLAGE: 9.1**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62  
 Stand: 17.06.2015



Seite: 1 von 2

**Manufacturer : RENAULT**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 47  
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1732	R1-1732	Without	66		610	1989	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 110 Nm

commercial type: **MEGANE SCENIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JZ	e2*2001/116*0379*..	63 -81	205/55R16 91H		1); 2); 33)
		63 -103	205/60R16 92H		
			205/60R16 96H		
JZ	e2*2007/46*0011*..	63 -81	205/55R16 91H		1); 2); 33)
		63 -96	205/60R16 92H		
			205/60R16 96H		

commercial type: **MEGANE,FLUENCE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Z	e2*2001/116*0373*..	63 -103	205/60R16 92		*) ; Fluence (Notchback); Front wheel drive; 1); 2); 33)
Z	e2*2001/116*0373*..	63 -103	205/55R16 91H		*) ; Hatchback; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0566-15-WIRD/N1  
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

**ANLAGE: 9.1**  
Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62  
Stand: 17.06.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.