

**Prüfbericht 366-0566-15-WIRD/N2****zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847****ANLAGE: 9.8**

Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62

Stand: 03.11.2015



Seite: 1 von 1

**Manufacturer : SUZUKI****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 CH Off set(mm) : 50

Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1947	R1-1947	Without	60		535	2025	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : SUZUKI**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 85 Nm

commercial type: **VITARA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
LY	e4*2007/46*0928*..	88	215/60R16 95		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.