

**Prüfbericht 366-0539-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000848**

ANLAGE: 9.5

Hersteller: MW Aftermarket Srl

Radtyp: 15605114-63

Stand: 06.08.2015



Seite: 1 von 1

**Manufacturer** : **HYUNDAI MOTOR (CZ)**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 CH Off set(mm) : 48

Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1901	R1-1901	Without	67		515	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : **HYUNDAI MOTOR (CZ)**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 110 Nm

commercial type: **IX20**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JC	e4*2007/46*0207*..	57-94	195/65R15 91H		1); 2); 33)
JC	e4*2007/46*0223*..	57-94	195/65R15 91H		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0539-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000848**

**ANLAGE: 9.6**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605114-63  
 Stand: 06.08.2015



Seite: 1 von 2

**Manufacturer : HYUNDAI MOTOR (CZ), KIA MOTORS (SK)**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 CH      Off set(mm) : 48  
 Hole circle (mm)/number of holes : 114,3/5      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1914	R1-1914	Without	67		515	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : HYUNDAI MOTOR (CZ)**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 107 Nm

commercial type: **VENGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
YN	e4*2007/46*0130*..	55-94	195/65R15 91H		1); 2); 33)
YN	e4*2007/46*0131*..	55-94	195/65R15 91H		1); 2); 33)
YNS	e4*2007/46*0261*..	55-94	195/65R15 91H		1); 2); 33)
YNS	e4*2007/46*0262*..	55-94	195/65R15 91H		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : KIA MOTORS (SK)**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 107 Nm

commercial type: **VENGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
YN	e4*2007/46*0130*..	55-94	195/65R15 91H		1); 2); 33)
YN	e4*2007/46*0131*..	55-94	195/65R15 91H		1); 2); 33)
YNS	e4*2007/46*0261*..	55-94	195/65R15 91H		1); 2); 33)
YNS	e4*2007/46*0262*..	55-94	195/65R15 91H		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0539-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000848**

**ANLAGE: 9.6**

Hersteller: MW Aftermarket Srl

Radtyp: 15605114-63

Stand: 06.08.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.