

**Prüfbericht 366-0556-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000849**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 29.07.2015



Seite: 1 von 2

**Manufacturer** : OPEL / VAUXHALL, RENAULT

**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2

Off set(mm) : 50

Hole circle (mm)/number of holes : 114,3/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1896	R1-1896	Without	66		850	2092	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : OPEL / VAUXHALL

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **VIVARO-B**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F7	e1*2007/46*0575*..	66-103	205/65R16C 107 215/65 R16C		*) ; from e1*2007/46*0575*12; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : RENAULT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

commercial type: **RENAULT TRAFIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
L	e2*2007/46*0014*..	66-103	205/65R16C 215/65R16C		*) ; Model 2015; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0556-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000849**

**ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 29.07.2015



Seite: 2 von 2

- 
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.