

**Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 1 von 3

Manufacturer : CITROEN, FIAT, PEUGEOT**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 68

Hole circle (mm)/number of holes : 118/5 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1908 | R1-1908 | Without | 71 | | 1000 | 2126 | 47/14 |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **CITROEN JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|--------|--------------------------|-----------------------|---|
| Y | e3*2001/116*0234*.. | 74-130 | 215/70R15C 225/70R15C | | *) to e3*2001/116*0234*10; 1); 2); 33); 6D) |
| Y | e3*2001/116*0234*.. | 81-130 | 215/70R15C 225/70R15C | | *) from e3*2001/116*0234*12; 1); 2); 33); 6D) |

commercial type: **JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|------------------|---|-----------------------|--|
| Y | e3*2007/46*0046*.. | 81-130 | 215/70R15C 225/70R15C | | *) from E3*2007/46*0046*10; 1); 2); 33); 6D) |
| Y | e3*2007/46*0046*.. | 74-110 74-130 | 205/70R15C 215/70R15C 225/70R15C 225/70R15C M+S | | *) to e3*2007/46*0046*06; 1); 2); 33); 6D) |
| YB | e2*2007/46*0252*.. | 81-110 | 205/70R15C 215/70R15C 225/70R15C 225/70R15C M+S | | *) to e2*2007/46*0252*03; 1); 2); 33) |
| YC | e2*2007/46*0254*.. | 81-110 | 205/70R15C 215/70R15C 225/70R15C 225/70R15C M+S | | *) bis e2*2007/46*0254*03; 1); 2); 33) |

Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850

ANLAGE: 9.2
 Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67
 Stand: 29.07.2015



Seite: 2 von 3

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **FIAT DUCATO**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|---------|----------------|-----------------------|--|
| 250 | e3*2001/116*0232*.. | 74 -116 | 215/70R15C | | *); ; 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 88 -116 | 225/70R15C | | |
| 250 | e3*2001/116*0232*.. | 83 -130 | 215/70R15C | | *); ; 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| 250 | e3*2007/46*0044*.. | 83 -130 | 215/70R15C | | *); from e3*2007/46*0044*13; 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 85 -109 | 205/70R15C | | |
| 250 | e3*2007/46*0049*.. | 96 -100 | 215/70R15C | | *); From e3*2007/46*0049*10; 1); 2); 33) |
| | | | 225/70R15C | | |
| 250 | e3*2007/46*0049*.. | 96 -130 | 215/70R15C 109 | | 1); 2); 33) |
| | | | 225/70R15C | | |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|------------|------------|-----------------------|---|
| Y | e3*2007/46*0045*.. | 81 -130 | 215/70R15C | | *); ; Lkw; Front wheel drive; 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| Y | e3*2007/46*0045*.. | 74 -110 | 205/70R15C | | *); to e3*2007/46*0045*05; Lkw; Front wheel drive; 1); 2); 33); 6D) |
| | | | 74 -130 | 215/70R15C | |
| | | 225/70R15C | | | |

commercial type: **PEUGEOT BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|---------|-----------------------|-----------------------|-----------------------------------|
| Y | e3*2001/116*0233*.. | 81 -130 | 215/70R15C | | *); ; 1); 2); 33); 6B); 6D) |
| | | | 225/70R15C | | |
| Y | e3*2001/116*0233*.. | 74 -130 | 215/70R15C 109 | | *); ; 1); 2); 33); 6B); 6D) |
| | | | 225/70R15C | | |
| | | | M+S 225/70R15C 112 | | |

**Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850****ANLAGE: 9.2**

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 3 von 3

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.
- 6B) Not for vehicle models which are solely equipped with 16-inch-wheels and which are only permissible for vehicle models till a permissible axle load of 2000 kg.
- 6D) Not for vehicle models which are solely equipped with 15-inch-wheels and which are only permissible for vehicle models till a permissible axle load of 2000 kg.

**Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 1 von 3

Manufacturer : CITROEN, FIAT, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 68

Hole circle (mm)/number of holes : 118/5 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|------------------------|--------------------|--------------------------------|---|-------------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1941 | R1-1941 | Without | 71 | | 1000 | 2126 | 47/14 |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **CITROEN JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|--------------------------|-----------------------|------------------|
| Y | e3*2001/116*0234*.. | 74 - 130 | 215/70R15C 225/70R15C | | 1); 2); 33); 6D) |
| Y | e3*2001/116*0234*.. | 81 - 130 | 215/70R15C 225/70R15C | | 1); 2); 33); 6D) |

commercial type: **JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|----------------------|---|-----------------------|------------------|
| Y | e3*2007/46*0046*.. | 81 - 130 | 215/70R15C 225/70R15C | | 1); 2); 33); 6D) |
| Y | e3*2007/46*0046*.. | 74 - 110 74 - 130 | 205/70R15C 215/70R15C 225/70R15C M+S | | 1); 2); 33); 6D) |
| YB | e2*2007/46*0252*.. | 81 - 110 | 205/70R15C 215/70R15C 225/70R15C M+S | | 1); 2); 33) |
| YB | e2*2007/46*0252*.. | 81 - 110 | 215/70R15C 225/70R15C | | 1); 2); 33) |
| YC | e2*2007/46*0254*.. | 81 - 110 | 205/70R15C 215/70R15C 225/70R15C M+S | | 1); 2); 33) |
| YC | e2*2007/46*0254*.. | 81 - 110 | 215/70R15C 225/70R15C | | 1); 2); 33) |

Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 2 von 3

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **FIAT DUCATO**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|----------------|-----------------------|---------------------------|
| 250 | e3*2001/116*0232*.. | 74 - 116 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 88 - 116 | 225/70R15C | | |
| 250 | e3*2001/116*0232*.. | 83 - 130 | 215/70R15C | | *); ; 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| 250 | e3*2007/46*0044*.. | 83 - 130 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 85 - 109 | 205/70R15C | | |
| 250 | e3*2007/46*0049*.. | 96 - 100 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| 250 | e3*2007/46*0049*.. | 96 - 130 | 215/70R15C 109 | | 1); 2); 33) |
| | | | 225/70R15C | | |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|----------|------------|-----------------------|--|
| Y | e3*2007/46*0045*.. | 81 - 130 | 215/70R15C | | *); Lkw; Front wheel drive; 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| Y | e3*2007/46*0045*.. | 74 - 110 | 205/70R15C | | *); Lkw; Front wheel drive; 1); 2); 33); 6D) |
| | | | 74 - 130 | 215/70R15C | |
| | | | 225/70R15C | | |

commercial type: **PEUGEOT BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|-----------------------|-----------------------|------------------|
| Y | e3*2001/116*0233*.. | 81 - 130 | 215/70R15C | | 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| Y | e3*2001/116*0233*.. | 74 - 130 | 215/70R15C 109 | | 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| | | | M+S 225/70R15C 112 | | |

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 3 von 3

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.
- 6D) Not for vehicle models which are solely equipped with 15-inch-wheels and which are only permissible for vehicle models till a permissible axle load of 2000 kg.

**Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 1 von 6

Manufacturer : CITROEN, FIAT, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 68
Hole circle (mm)/number of holes : 118/5 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|------------------------|--------------------|--------------------------------|---|-------------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1635 | R1-1635 | Without | 71 | | 1000 | 2112 | 47/14 |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 250L; Y; 250; 250D

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : 230L;
244 M; YB; 23; 230P; 244; 230D; 244 D; Z; 244 L; 230; YC; Y

Tightening torque for fixing parts : 160 Nm

commercial type: **CITROEN JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions | |
|--------------|---------------------|---------|------------|-----------------------|---|-----------|
| Y | e3*2001/116*0234*.. | 81 -130 | 215/70R15C | | 1); 2); 33); 6D) | |
| | | | 225/70R15C | | | |
| Y | e3*2001/116*0234*.. | 74 -130 | 215/70R15C | | 1); 2); 33); 6D) | |
| | | | 225/70R15C | | | |
| Z | e3*98/14*0104*.. | 62 -94 | 195/70R15 | | 1); 2); 33); 6D) | |
| | | | 205/70R15 | | | |
| 23 | e3*96/27*0027*.. | 50 -80 | 215/65R15 | | 1); 2); 33) | |
| | | | 50 -94 | | | 195/70R15 |
| | | | | | | 205/70R15 |
| | | | 93 -94 | | | 215/70R15 |
| 230 | G712 | 50 -94 | 195/70R15 | | 1); 2); 33); 6D) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 230D | G831 | 62 -94 | 195/70R15 | | *); Lkw; Front wheel drive; zul. GesGew. 2800 bzw. 3200 kg; 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 230L | G713 | 50 -94 | 195/70R15 | | 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 230P | G714 | 63 -80 | 195/70R15 | | 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |

Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 2 von 6

commercial type: **CITROEN JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|----------|------------|----------------|-----------------------|--|
| 244 | K908 | 62 | 195/70R15 | | 1); 2); 33) |
| | | 62 -94 | 205/70R15 | | |
| | | | 215/70R15 | | |
| 244 D | K907 | 62 -94 | 205/70R15 | | 1); 2); 33) |
| | | | 215/70R15 | | |
| 244 L | K909 | 62 -94 | 195/70R15 | | 1); 2); 33) |
| | | | 205/70R15 | | |
| 244 M | L114 | 71 -81 | 205/70R15C | | 1); 2); 33) |
| 250 | L774 | 74 -88 | 205/70R15C 106 | | 1); 2); 33); 6D) |
| | | | 215/70R15C 109 | | |
| | | | 225/70R15C 112 | | |
| 250 | L774 | 74 -88 | 205/70R15C 106 | | 1); 2); 33); 6D) |
| | | | 215/70R15C 109 | | |
| | | 74 -116 | 225/70R15C 112 | | |
| 250D | L939 | 74 -116 | 215/70R15C | | *); Lkw offener Kasten (Serie); 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| 250L | L773 | 74 -88 | 205/70R15C | | 1); 2); 33); 6D) |
| | | | 74 -116 | 215/70R15C | |
| | | 225/70R15C | | | |

commercial type: **JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|-------------------|-------------------|-----------------------|------------------|
| Y | e3*2007/46*0046*.. | 81 -130 | 215/70R15C | | 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| Y | e3*2007/46*0046*.. | 74 -110 | 205/70R15C | | 1); 2); 33); 6D) |
| | | | 74 -130 | 215/70R15C | |
| | | 225/70R15C | | | |
| | | 225/70R15C M+S | | | |
| YB | e2*2007/46*0252*.. | 81 -110 | 205/70R15C | | 1); 2); 33) |
| | | | 215/70R15C | | |
| | | | 225/70R15C | | |
| | | | 225/70R15C M+S | | |
| YB | e2*2007/46*0252*.. | 81 -110 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| YC | e2*2007/46*0254*.. | 81 -110 | 205/70R15C | | 1); 2); 33) |
| | | | 215/70R15C | | |
| | | | 225/70R15C | | |
| | | | 225/70R15C M+S | | |
| YC | e2*2007/46*0254*.. | 81 -110 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 3 von 6

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 250D; 250; 250L

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 230 M; 230; 250; 230P; 244; 244 D; 230D; 230L; 244 M;
244 L; 250M

Tightening torque for fixing parts : 160 Nm

commercial type: **FIAT DUCATO**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|---------|------------|-----------------------|---|
| 230 | e3*96/27*0025*.. | 50 -90 | 195/70R15 | | 1); 2); 33) |
| | | | 215/65R15 | | |
| | | 50 -94 | 195/70R15 | | |
| | | | 205/70R15 | | |
| 93 -94 | 215/70R15 | | | | |
| 230 | G687 | 50 -85 | 195/70R15 | | *); Lkw; Front wheel drive; 1); 2); 33) |
| | | 50 -94 | 215/70R15 | | |
| | | 59 -85 | 205/70R15 | | |
| 230 M | K861 | 70 -80 | 195/70R15 | | 1); 2); 33); 6D) |
| | | | 205/70R15 | | |
| | | | 215/70R15 | | |
| 230D | G830 | 62 -94 | 195/70R15 | | 1); 2); 33); 6D) |
| | | | 205/70R15 | | |
| | | | 215/70R15 | | |
| 230L | G688 | 50 -94 | 195/70R15 | | *); not for FZ with ZGG=3500 kg; 1); 2); 33); 6D) |
| | | | 205/70R15 | | |
| | | | 215/70R15 | | |
| 230P | G715 | 51 -85 | 195/70R15 | | 1); 2); 33) |
| | | | 205/70R15 | | |
| | | | 215/70R15 | | |
| 244 | e3*98/14*0102*.. | 62 -94 | 195/70R15 | | 1); 2); 33); 6D) |
| | | | 205/70R15 | | |
| 244 | K916 | 62 | 195/70R15 | | 1); 2); 33) |
| | | 62 -94 | 205/70R15 | | |
| | | | 215/70R15 | | |
| 244 D | K918 | 62 -94 | 205/70R15 | | 1); 2); 33) |
| | | | 215/70R15 | | |
| 244 L | K917 | 62 -94 | 195/70R15 | | 1); 2); 33); 6D) |
| | | 62 -107 | 205/70R15 | | |
| 244 M | L094 | 71 -81 | 205/70R15C | | 1); 2); 33) |
| 250 | e3*2001/116*0232*.. | 74 -116 | 215/70R15C | | 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| | | 88 -116 | 225/70R15C | | |
| 250 | e3*2001/116*0232*.. | 74 -116 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 88 -116 | 225/70R15C | | |
| 250 | e3*2001/116*0232*.. | 83 -130 | 215/70R15C | | 1); 2); 33); 6D) |
| | | | 225/70R15C | | |

Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 4 von 6

commercial type: **FIAT DUCATO**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|---------|----------------|-----------------------|--|
| 250 | e3*2007/46*0044*.. | 83 -130 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 85 -109 | 205/70R15C | | |
| 250 | e3*2007/46*0044*.. | 83 -109 | 205/70R15C 106 | | 1); 2); 33) |
| | | | 225/70R15C | | |
| | | 83 -130 | 215/70R15C 109 | | |
| 250 | e3*2007/46*0049*.. | 96 -100 | 215/70R15C | | 1); 2); 33) |
| | | | 225/70R15C | | |
| 250 | e3*2007/46*0049*.. | 96 -130 | 215/70R15C 109 | | 1); 2); 33) |
| | | | 225/70R15C | | |
| 250 | L778 | 74 -116 | 205/70R15 | | 1); 2); 33); 6D) |
| | | | 215/70R15 | | |
| | | | 225/70R15 | | |
| 250D | L968 | 74 -116 | 215/70R15C | | *); Lkw offener Kasten (Serie); 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| 250L | L779 | 74 -88 | 205/70R15C | | 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| | | 74 -116 | 215/70R15C | | |
| 250M | N413 | 100 | 215/70R15C 106 | | 1); 2); 33) |
| | | | 225/70R15C 109 | | |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : Y; 250L; 250; 250D

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 244 M; 230; 230P; 244 D; 244; 230D; 230L; 244 L; Z; Y; 23

Tightening torque for fixing parts : 160 Nm

commercial type: **BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|---------|------------|-----------------------|--|
| Y | e3*2007/46*0045*.. | 74 -110 | 205/70R15C | | *); Lkw; Front wheel drive; 1); 2); 33); 6D) |
| | | | 215/70R15C | | |
| | | 74 -130 | 225/70R15C | | |
| Y | e3*2007/46*0045*.. | 81 -130 | 215/70R15C | | *); Lkw; Front wheel drive; 1); 2); 33); 6D) |
| | | | 225/70R15C | | |
| 250D | L936 | 74 -116 | 215/70R15C | | *); Lkw offener Kasten (Serie); 1); 2); 33); 6D) |
| | | | 225/70R15C | | |

Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 5 von 6

commercial type: **PEUGEOT BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions | |
|--------------|---------------------|---------|----------------|-----------------------|------------------|--|
| Y | e3*2001/116*0233*.. | 74 -130 | 215/70R15C 109 | | 1); 2); 33); 6D) | |
| | | | 225/70R15C | | | |
| | | | 225/70R15C 112 | | | |
| Z | e3*98/14*0103*.. | 62 -94 | 195/70R15 | | 1); 2); 33); 6D) | |
| | | | 205/70R15 | | | |
| 23 | e3*96/27*0026*.. | 50 -80 | 215/65R15 | | 1); 2); 33) | |
| | | | 50 -94 | 195/70R15 | | |
| | | | 205/70R15 | | | |
| 230 | G716 | 50 -94 | 195/70R15 | | 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 230D | G828 | 62 -94 | 195/70R15 | | 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 230L | G717 | 50 -94 | 195/70R15 | | 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 230P | G718 | 63 -80 | 195/70R15 | | 1); 2); 33) | |
| | | | 205/70R15 | | | |
| | | | 215/70R15 | | | |
| 244 | K913 | 62 | 195/70R15 | | 1); 2); 33) | |
| | | | 62 -94 | 205/70R15 | | |
| | | | 215/70R15 | | | |
| 244 D | K914 | 62 -94 | 205/70R15 | | 1); 2); 33) | |
| | | | 215/70R15 | | | |
| 244 L | K912 | 62 -94 | 195/70R15 | | 1); 2); 33); 6D) | |
| | | | 62 -107 | 205/70R15 | | |
| 244 M | L113 | 71 -81 | 205/70R15C | | 1); 2); 33) | |
| 250 | L771 | 74 -88 | 205/70R15 | | 1); 2); 33); 6D) | |
| | | | 74 -116 | 215/70R15C | | |
| | | | 225/70R15 | | | |
| 250L | L772 | 74 -88 | 205/70R15C | | 1); 2); 33); 6D) | |
| | | | 74 -116 | 215/70R15C | | |
| | | | 225/70R15C | | | |

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

**Prüfbericht 366-0540-15-WIRD
zur Erteilung der ECE (E1) 124R- 000850**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605118-67

Stand: 29.07.2015



Seite: 6 von 6

- 6D) Not for vehicle models which are solely equipped with 15-inch-wheels and which are only permissible for vehicle models till a permissible axle load of 2000 kg.