

**Prüfbericht 366-0557-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000851**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605118-68

Stand: 29.04.2015



Seite: 1 von 3

**Manufacturer** : NISSAN, OPEL, OPEL / VAUXHALL, RENAULT

**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2

Off set(mm) : 50

Hole circle (mm)/number of holes : 118/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1373	R1-1373	Without	71,1		850	2130	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : NISSAN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

commercial type: **NISSAN PRIMASTAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F4	K995	60-99	195/65R16C		1); 2); 33)
		60-107	205/65R16C 103T		
			215/65R16C 109		
J4	e2*98/14*0271*..	60-87	195/65R16C		1); 2); 33)
			205/65R16C M+S		
			205/65R16C 103T		
			60-99	195/75R16C 107	
		60-107	215/65R16C 109		

commercial type: **PRIMASTAR, NV300**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
4	e2*2007/46*0037*..	66-86	195/65R16C 104/102		1); 2); 33)
			205/65R16C 107		
			66-107	215/65R16C 106	

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : OPEL, OPEL / VAUXHALL

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

**Prüfbericht 366-0557-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000851**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605118-68

Stand: 29.04.2015



Seite: 1 von 3

**Manufacturer** : NISSAN, OPEL, OPEL / VAUXHALL, RENAULT

**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2

Off set(mm) : 50

Hole circle (mm)/number of holes : 118/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1373	R1-1373	Without	71,1		850	2130	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : NISSAN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

commercial type: **NISSAN PRIMASTAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F4	K995	60-99	195/65R16C		1); 2); 33)
		60-107	205/65R16C		
			103T 215/65R16C 109		
J4	e2*98/14*0271*..	60-87	195/65R16C		1); 2); 33)
			205/65R16C		
			M+S 205/65R16C		
			103T		
		60-99	195/75R16C 107		
60-107	215/65R16C 109				

commercial type: **PRIMASTAR, NV300**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
4	e2*2007/46*0037*..	66-86	195/65R16C		1); 2); 33)
			104/102		
			205/65R16C 107		
66-107	215/65R16C 106				

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : OPEL, OPEL / VAUXHALL

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

**Prüfbericht 366-0557-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000851**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605118-68

Stand: 29.04.2015



Seite: 2 von 3

commercial type: **VIVARO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E7	L048	66 -86	205/65R16C 107		1); 2); 33)
		84 -107	215/65R16C 106/104		
F7	e1*2007/46*0575*..	66 -86	195/65R16C		1); 2); 33)
		66 -107	205/65R16C		
			205/65R16C 103 M+S 215/65R16C		
F7	K830	60 -99	195/65R16C		1); 2); 33)
		60 -107	205/65R16C		
			215/65R16C 109		
X83	e1*98/14*0170*..	60 -99	195/65R16C		*); ; 1); 2); 33)
		60 -107	195/75R16C		
			205/65R16C		
			215/65R16C 109		
84 -107	205/65R16C M+S				

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

commercial type: **RENAULT TRAFIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FL	K833	60 -99	195/65R16C		1); 2); 33)
		60 -107	205/65R16C 103T		
			215/65R16C 109		
JL	e2*98/14*0213*..	60 -88	205/65R16C		1); 2); 33)
		60 -99	195/65R16C		
			205/65R16C 103T		
		60 -107	195/75R16C 215/65R16C 109		
L	e2*2007/46*0014*..	66 -86	195/65R16C 104/102		1); 2); 33)
			205/65R16C 107		
		66 -107	215/65R16C 106		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments