

**Prüfbericht 366-0558-15-WIRD
zur Erteilung der ECE (E1) 124R- 000852**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-70

Stand: 29.04.2015



Seite: 1 von 4

Manufacturer : CITROEN, FIAT, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 68
Hole circle (mm)/number of holes : 130/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1636	R1-1636	Without	78,1		1200	2255	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad, for Type : 250D; 250; Y; 250L

Accessories : Serie

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad, for Type : 230D; 230L; 230; 244 D; Y; YD; 244 B; 244 M; 244 L; 244

Tightening torque for fixing parts : 180 Nm

commercial type: **CITROEN JUMPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2001/116*0234*..	88 -130	215/75R16C 225/75R16C		*) ; langer Radstand; 1); 2); 1D); 33)
230	G712	63 -94	205/75R16 215/75R16		1); 2); 33)
230D	G831	63 -94	205/75R16 215/75R16		*) ; Lkw, Front wheel drive; zul. GesGew. 3500 kg; 1); 2); 33)
230L	G713	63 -94	205/75R16 215/75R16		1); 2); 33)
244	K908	74 -94	205/75R16 215/75R16		1); 2); 33)
244 B	L306	71 -94	205/75R16C 215/75R16C		1); 2); 33)
244 D	K907	74 -94	205/75R16 215/75R16		1); 2); 33)
244 L	K909	74 -94	205/75R16 215/75R16		1); 2); 33)
244 M	L114	71 -81	205/75R16C 215/75R16C		1); 2); 33)
250	L774	88 -116	215/75R16-99 225/75R16		1); 2); 1D); 33)

**Prüfbericht 366-0558-15-WIRD
zur Erteilung der ECE (E1) 124R- 000852**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-70

Stand: 29.04.2015



Seite: 2 von 4

commercial type: **CITROEN JUMPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
250D	L939	88 -116	215/75R16C		*); Lkw offener Kasten (Serie); 1); 2); 1D); 33)
			225/75R16C		
250L	L773	88 -116	215/75R16C		1); 2); 1D); 33)
			225/75R16C		

commercial type: **JUMPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0046*..	88 -130	215/75R16C		1); 2); 33)
			225/75R16C		
			225/75R16C		
			M+S		

commercial type: **JUMPER Cabine Approfondie**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
YD	e2*2007/46*0256*..	96 -110	215/75R16C		1); 2); 33)
			225/75R16C		
			225/75R16C		
			M+S		

commercial type: **JUMPER, RELAY**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0051*..	96 -130	215/75R16C		1); 2); 33)
			225/75R16C		
			225/75R16C		
			M+S		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad,
for Type : 250D; 250; 250L

Accessories : Serie

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad,
for Type : 244 M; 230L; 244 D; 230; 244; 250 M; 250; 230 M; 244 B;
244 L; 230D

Tightening torque for fixing parts : 180 Nm

commercial type: **FIAT DUCATO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
230	G687	62 -94	205/75R16		*); Lkw, Front wheel drive; 1); 2); 33)
			215/75R16		
230 M	K861	70 -80	205/75R16		1); 2); 33)
			215/75R16		
230D	G830	62 -94	205/75R16		1); 2); 33)
			215/75R16		

**Prüfbericht 366-0558-15-WIRD
zur Erteilung der ECE (E1) 124R- 000852**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-70

Stand: 29.04.2015



Seite: 3 von 4

commercial type: **FIAT DUCATO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
230L	G688	62 -94	205/75R16 215/75R16		*) ; only for FZ with ZGG=3500 kg; 1); 2); 33)
244	K916	81 -94	205/75R16 215/75R16		1); 2); 33)
244 B	L051	81 -94	205/75R16C 215/75R16C		1); 2); 33)
244 D	K918	81 -94	205/75R16 215/75R16		1); 2); 33)
244 L	K917	81 -107	205/75R16 215/75R16		1); 2); 33)
244 M	L094	71 -81	205/75R16C 215/75R16C		1); 2); 33)
250	e3*2001/116*0232*..	88 -130	215/75R16C 225/75R16C		1); 2); 1D); 33)
250	e3*2001/116*0232*..	88 -116	215/75R16C 225/75R16C		1); 2); 33)
250	e3*2007/46*0044*..	96 -130	215/75R16C 225/75R16C		*) ; langer Radstand; 1); 2); 33)
250	e3*2007/46*0049*..	96 -130	215/75R16C 225/75R16C		*) ; langer Radstand; 1); 2); 1D); 33)
250	L778	88 -116	225/75R16		1); 2); 1D); 33)
250D	L968	88 -116	215/75R16C 225/75R16C		*) ; Lkw offener Kasten (Serie); 1); 2); 1D); 33)
250L	L779	88 -116	215/75R16C 225/75R16C		1); 2); 1D); 33)

commercial type: **FIAT Ducato Natural Power**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
250 M	N413	100	215/75R16C 116/114 225/75R16C 118/116		1); 2); 1D); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad,
for Type : 250D; 250; Y; 250L

Accessories : Serie

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad,
for Type : 230D; 230L; 244; 244 D; 230P; 244 M; 244 L; Y; 230

Tightening torque for fixing parts : 180 Nm

Prüfbericht 366-0558-15-WIRD
zur Erteilung der ECE (E1) 124R- 000852

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-70

Stand: 29.04.2015



Seite: 4 von 4

commercial type: **BOXER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0045*..	96 -130	215/75R16C 225/75R16C		*) ; langer Radstand; 1); 2); 33)
Y	e3*2007/46*0050*..	96 -130	215/75R16C 225/75R16C		*) ; langer Radstand; 1); 2); 33)
250D	L936	88 -116	215/75R16C 225/75R16C		*) ; Lkw offener Kasten (Serie); 1); 2); 1D); 33)

commercial type: **PEUGEOT BOXER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2001/116*0233*..	88 -130	215/75R16C 225/75R16C		*) ; not short axle; 1); 2); 1D); 33)
230	G716	63 -94	205/75R16 215/75R16		1); 2); 33)
230D	G828	63 -94	205/75R16 215/75R16		1); 2); 33)
230L	G717	63 -94	205/75R16 215/75R16		1); 2); 33)
230P	G718	63 -80	205/75R16 215/75R16		1); 2); 33)
244	K913	74 -94	205/75R16 215/75R16		1); 2); 33)
244 D	K914	74 -94	205/75R16 215/75R16		1); 2); 33)
244 L	K912	74 -107	205/75R16 215/75R16		1); 2); 33)
244 M	L113	71 -81	205/75R16C 215/75R16C		1); 2); 33)
250	L771	88 -116	215/75R16 225/75R16		1); 2); 1D); 33)
250L	L772	88 -116	215/75R16C 225/75R16C		1); 2); 1D); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 1D) The permissible axle load of the must not exceed 2400kg in consideration of the rolling circumference (see examined wheel load in this report I. Overview).
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.