

**Prüfbericht 366-0326-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001036**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655120-69

Stand: 23.09.2015



Seite: 1 von 3

**Manufacturer : VOLKSWAGEN****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 51

Hole circle (mm)/number of holes : 120/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1529	R1-1529	Without	65		923	2092	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, diameter 28 mm

Tightening torque for fixing parts : 180 Nm

commercial type: **CALIFORNIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7HMA	e1*2001/116*0289*..	75-110	205/65R16C 215/65R16C		*) ; from e1*2001/116*0289*25; T6; 1); 2); 33)

commercial type: **TRANSPORTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7J0	e1*2007/46*0130*..	62-110	205/65R16C 215/65R16C		*) ; up to e1*2007/46*0130*15; Lkw box van (series); pickup truck (series); Lorry body with cab; all-wheel drive; Front wheel drive; 1); 2); 33)
7J0	e1*2007/46*0130*..	62-110	205/65R16C 215/65R16C		*) ; T6; from e1*2007/46*0130*16; Lkw box van (series); pickup truck (series); Lorry body with cab; 1); 2); 33)

**Prüfbericht 366-0326-15-WIRD  
zur Erteilung der ECE (E1) 124R- 001036**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655120-69

Stand: 23.09.2015



Seite: 2 von 3

commercial type: **TRANSPORTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7J0	e1*2007/46*0130*..	62 -103	205/65R16C 103		*); Lkw box van (series); pickup truck (series); Lorry body with cab; all-wheel drive; Front wheel drive; 1); 2); 33)
			215/65R16C 102/100		
7J0	e1*2007/46*0130*..	62 -150	205/65R16 103		1); 2); 33)
			215/65R16 102		
7J0	L225	62 -128	205/65R16C 103T		*); pickup truck (series); Lorry body with cab; short wheel base; long wheel base; all-wheel drive; Front wheel drive; 1); 2); 33)
			215/65R16C 109		

commercial type: **TRANSPORTER, CALIFORNIA, MULTIVAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7HC	e1*2001/116*0220*..	62 -128	205/65R16C		*); up to e1*2001/116*0220*35; 1); 2); 33)
			215/65R16C 109		
7HC	e1*2001/116*0220*..	62 -110	205/65R16C		*); T6; from e1*2001/116*0220*36; 1); 2); 33)
			215/65R16C		
7HCA	e1*2001/116*0286*..	96 -128	205/65R16C 103		1); 2); 33)
			215/65R16C 102/100		
			215/65R16C 106/104		
7HK	L148	63 -128	205/65R16C		1); 2); 33)
			215/65R16C 109		
7HKX0	L148	63 -128	205/65R16C 103T		1); 2); 33)
			215/65R16C 109		
7HM	e1*2001/116*0218*..	62 -96	205/65R16C 103T		1); 2); 33)
		62 -128	215/65R16C 109		
		128	205/65R16C 103 M+S		
7HMA	e1*2001/116*0289*..	62 -103	205/65R16C 103T		*); Only to e1*2001/116*0289*10; 1); 2); 33)
		62 -128	215/65R16C 102/100		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Prüfbericht 366-0326-15-WIRD  
zur Erteilung der ECE (E1) 124R- 001036**

**ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 16655120-69

Stand: 23.09.2015



Seite: 3 von 3

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.