

**Prüfbericht 366-0374-15-WIRD  
zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 1 von 2

**Manufacturer** : SEAT, SKODA, VOLKSWAGEN

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 43

Hole circle (mm)/number of holes : 112/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1850	R1-1850	Without	57		615	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : SEAT

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **LEON / LEON SC / LEON ST / LEON X-PERIENCE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5F	e9*2007/46*0094*..	63 -110	195/65R15		*) ; from e9*2007/46*0094*01; all-wheel drive; Front wheel drive; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : SKODA

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5E	e11*2007/46*0243*..	63 -81	195/65R15		*) ; all-wheel drive; Front wheel drive; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : VOLKSWAGEN

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

**Prüfbericht 366-0374-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 2 von 2

commercial type: **GOLF, GOLF VARIANT, GOLF SPORTSVAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AU	e1*2007/46*0623*..	63 -81	195/65R15		1); 2); 33)
		90 -110	195/65R15		

commercial type: **GOLF, GOLF VARIANT, GOLF SPORTSVAN, GOLF ALLTRACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AUV	e1*2007/46*0627*..	63 -110	195/65R15		1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.