

**Prüfbericht 366-0374-15-WIRD  
zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 1 von 5

**Manufacturer** : SEAT, SKODA, VOLKSWAGEN

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 47

Hole circle (mm)/number of holes : 112/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1489	R1-1489	Without	57		650	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : SEAT

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **ALTEA, ALTEA XL, FREETRACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5PN	e9*2007/46*0012*..	63 -77	195/65R15 91		1); 2); 33)
		92 -100	195/65R15 91H		
		103 -118	195/65R15-91V		

commercial type: **ALTEA, ALTEA XL, TOLEDO, FREETRACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5P	e9*2001/116*0050*..	63 -110	195/65R15	from NT*23	*); Altea; Altea XL; Toledo; 1); 2); 33)
		118	195/65R15	from NT*24	
5P	e9*2001/116*0050*..	77 -92	195/65R15 91		*); Altea Freetrack; 1); 2); 33)

commercial type: **LEON**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1P	e9*2001/116*0052*..	63 -110	195/65R15 91		1); 2); 33)
			M+S		
			195/65R15 91H		
		103 -118	195/65R15-91V		

commercial type: **LEON / LEON SC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5F	e9*2007/46*0094*..	103	195/65R15 91		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : SKODA

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

**Prüfbericht 366-0374-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 2 von 5

Tightening torque for fixing parts : 120 Nm

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1Z	e11*2001/116*0230*..	59	195/65R15 91		*); from e11*2001/116*0230*29; 1); 2); 33)
		75-90	195/65R15 91H		
		77	195/65R15 91 M+S		
		81-118	195/65R15-91V		
1Z	e11*2001/116*0230*..	55-118	195/65R15		1); 2); 33)
1Z	e11*2007/46*0012*..	59	195/65R15 91		1); 2); 33)
		75-90	195/65R15 91H		
		81-118	195/65R15-91V		
5E	e11*2007/46*0243*..	63-81	195/65R15		*); all-wheel drive; Front wheel drive; 1); 2); 33)
5E	e11*2007/46*0244*..	77	195/65R15 91H		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **CADDY**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2K	e1*2001/116*0252*..	51-59	195/65R15		*); to NT*27;
		77	195/65R15		1); 2); 33)
2K	e1*2001/116*0252*..	55-81	195/65R15 91		*); from NT*28;
		80-81	195/65R15 95		1); 2); 33)

commercial type: **GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AUV	e1*2007/46*0627*..	90	195/65R15 91H 205/50R15 91H		1); 2); 33)
1K	e1*2001/116*0242*..	90-103	195/65R15 91H		1); 2); 33)
			205/60R15-91H		
1K	e1*2001/116*0242*..	59-81	195/65R15 91		*); Only Golf 6; from e1*2001/116*0242*25; not all-wheel drive; 1); 2); 33)
			205/60R15 91		
		81-103	195/65R15 91H		
			205/60R15-91H		
1K	e1*2001/116*0242*..	77-103	195/65R15 91		*); Cabrio; 1); 2); 33)
			205/60R15 91		
1K	e1*2001/116*0242*..	55-66	195/65R15 91		*); Only Golf 5; only to e1*2001/116*0242*24; 1); 2); 33)
			205/60R15 91		
		55-110	205/60R15-91H		
		66-110	195/65R15 91H		
		100-110	195/65R15-91V 205/60R15-91V		

**Prüfbericht 366-0374-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 3 von 5

commercial type: **GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1K	e1*2007/46*0490*..	66 -77	205/60R15 91		1); 2); 33)
		90 -103	205/60R15-91H		

commercial type: **GOLF PLUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1KP	e1*2001/116*0304*..	59 -103	195/65R15 91		*); Only Golf Plus 6; From e1*2001/116*0304*14; 1); 2); 33)
			205/60R15 91		
1KP	e1*2001/116*0304*..	55 -77	195/65R15 91		*); Only Golf Plus 5; Only to e1*2001/116*0304*13; 1); 2); 33)
			205/60R15 91		
		55 -110	195/65R15 91H		
			205/60R15-91H		
96 -110	195/65R15-91V				
	205/60R15-91V				
1KP	e1*2001/116*0304*..	75 -77	195/65R15 91		*); Only CrossGolf; Only CrossGolf 5; 1); 2); 33)
			205/60R15 91		
		90 -103	195/65R15 91H		
205/60R15-91H					
1KP	e1*2001/116*0304*..	77 -90	195/65R15 91		*); Only CrossGolf 6; From e1*2001/116*0304*21; 1); 2); 33)
			205/60R15 91		

commercial type: **JETTA, BEETLE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
16	e1*2007/46*0539*..	77	195/65R15-91T		*); Not Beetle (Hatchback); 1); 2); 33)
			205/60R15-91T		
		90 -110	195/65R15 91H		
205/60R15-91H					

commercial type: **JETTA, GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1KM	e1*2001/116*0328*..	59 -103	195/65R15		*); Golf 5 (Variant); only to e1*2001/116*0328*14; not all-wheel drive; 1); 2); 33)
			205/60R15		
1KM	e1*2001/116*0328*..	59 -90	195/65R15		*); GOLF 6 (Variant); from e1*2001/116*0328*15; not all-wheel drive; 1); 2); 33)
			205/60R15		
1KM	e1*2001/116*0328*..	75 -110	195/65R15		*); JETTA (Limousine); only to e1*2001/116*0328*14; 1); 2); 33)
			205/60R15		

**Prüfbericht 366-0374-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 4 von 5

commercial type: **JETTA, GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1KM	e1*2001/116*0328*..	66 -103	195/65R15 205/60R15		*) ; JETTA (Limousine); from e1*2001/116*0328*15; 1); 2); 33)

commercial type: **TOURAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1t	DE*2007/46*0506*..	66 -77 103	195/65R15 91 195/65R15 91H		1); 2); 33)
1t	DE*2007/46*0506*..	77 -103	195/65R15 91 M+S		*) ; only CrossTouran; 1); 2); 33)
1t	e1*2007/46*0506*..	66 -77 103	195/65R15 195/65R15	not Dieselmotor	*) ; Touran; 1); 2); 33)
1t	e1*2007/46*0506*..	77 103	195/65R15 M+S 195/65R15 M+S	not Dieselmotor	*) ; only CrossTouran; 1); 2); 33)
1T	e1*2001/116*0211*..	75 77 -103	195/65R15 91 M+S 195/65R15 95 M+S		*) ; only CrossTouran; from NT*15 to NT*23; 1); 2); 33)
1T	e1*2001/116*0211*..	77 -103	195/65R15 91 M+S		*) ; only CrossTouran; from e1*2001/116*0211*23; 1); 2); 33)
1T	e1*2001/116*0211*..	66 -80 75 -103 77 77 -103 100 -103 103	195/65R15 91 195/65R15 91 M+S 195/65R15 95 195/65R15-89 195/65R15-95T M+S 195/65R15 91H 195/65R15 95H		*) ; from NT e1*2001/116*0211*13; 1); 2); 33)
1T	e1*2007/46*0357*..	77 103	195/65R15 M+S 195/65R15 M+S		*) ; only CrossTouran; to e1*2007/46*0357*01; 1); 2); 33)
1T	e1*2007/46*0357*..	66 77 103	195/65R15 195/65R15 195/65R15		*) ; from e1*2007/46*0357*02; Touran; 1); 2); 33)
1T	e1*2007/46*0357*..	77 103	195/65R15 91 195/65R15 95 195/65R15 91H		*) ; from e1*2007/46*0357*02; 1); 2); 33)

**Prüfbericht 366-0374-15-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001037**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605112-57

Stand: 05.11.2015



Seite: 5 von 5

commercial type: **TOURAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1T	e1*2007/46*0357*..	66 -77	195/65R15 M+S		*); only CrossTouran; from e1*2007/46*0357*02; 1); 2); 33)
		103	195/65R15 91 M+S		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.