

**Prüfbericht 366-0083-16-WIRD
zur Erteilung der ECE (E1) 124R- 001038**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605098-36

Stand: 02.03.2016



Seite: 1 von 2

Manufacturer : FIAT, OPEL / VAUXHALL

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 39

Hole circle (mm)/number of holes : 98/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1742	R1-1742	Without	58		575	1937	47/14
R1-1743	R1-1743	Without	58		575	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 263

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : 199

Tightening torque for fixing parts : 90 Nm for Type : 263
110 Nm for Type : 199

commercial type: **FIAT DOBLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
263	e3*2007/46*0007*..	66-77	185/65R15 88 195/65R15		1); 2); 33)

commercial type: **FIAT PUNTO, PUNTO ABARTH, FIAT 500L**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
199	e3*2001/116*0217*..	62-77	195/65R15 91H		*) ; Fiat 500L; Hatchback; Front wheel drive; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : OPEL / VAUXHALL

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **COMBO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Combo-D	e3*2007/46*0079*..	66-77	185/65R15 88 195/65R15-95T		*) ; not 70kW; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Prüfbericht 366-0083-16-WIRD
zur Erteilung der ECE (E1) 124R- 001038**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605098-36

Stand: 02.03.2016



Seite: 2 von 2

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.