

**Prüfbericht 366-0074-16-WIRD
zur Erteilung der ECE (E1) 124R- 001045**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 14605100-40

Stand: 25.02.2016



Seite: 1 von 2

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 J X 14 H2 Off set(mm) : 43

Hole circle (mm)/number of holes : 100/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1200	R1-1200	Without	57		508	1763	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **IBIZA,CORDOBA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6L	e9*2001/116*0041*..	44 -63	185/60R14 82		1); 2); 33)
		44 -77	185/60R14-82T M+S		
		51 -77	185/60R14-82H		
6L	e9*98/14*0041*..	47 -55	185/60R14		1); 2); 33)
		47 -74	185/60R14-82H		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **FABIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6Y	e11*98/14*0123*..	37 -59	185/60R14 82		1); 2); 33)
		37 -74	185/60R14-82H		

commercial type: **FABIA PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6Y	L164	47 -51	185/60R14 82		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Prüfbericht 366-0074-16-WIRD
zur Erteilung der ECE (E1) 124R- 001045

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 14605100-40

Stand: 25.02.2016



Seite: 2 von 2

Tightening torque for fixing parts : 120 Nm

commercial type: **FOX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5Z	e1*2001/116*0301*..	40 -55	185/60R14 82		1); 2); 33)
			185/60R14-82H		

commercial type: **VW POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9N	e1*2001/116*0174*..	40 -63	185/60R14 82		1); 2); 33)
		74	185/60R14-82H		
9N	e1*2001/116*0174*..	40 -63	185/60R14 82		*) ; from Nachtr.
		74 -77	185/60R14-82H		e1*2001/116*0174*12; 1); 2); 33)
9N	e1*98/14*0174*..	40 -74	185/60R14		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.