

Prüfbericht 366-0345-15-WIRD
zur Erteilung der ECE (E1) 124R- 001046

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-78

Stand: 07.10.2015



Seite: 1 von 2

Manufacturer : CITROEN, FIAT, PEUGEOT**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 68
 Hole circle (mm)/number of holes : 130/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1910	R1-1910	Without	78		1280	2269	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 180 Nm

commercial type: **CITROEN JUMPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2001/116*0234*..	88 - 130	215/75R16C 225/75R16C		*) ; long wheel base; 1); 2); 33)

commercial type: **JUMPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0046*..	88 - 130	215/75R16C 225/75R16C 225/75R16C M+S		1); 2); 33)

commercial type: **JUMPER, RELAY**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0051*..	96 - 130	215/75R16C 225/75R16C 225/75R16C M+S		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 180 Nm

commercial type: **FIAT DUCATO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
250	e3*2001/116*0232*..	88 - 130	215/75R16C 225/75R16C		1); 2); 33)

Prüfbericht 366-0345-15-WIRD
zur Erteilung der ECE (E1) 124R- 001046

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-78

Stand: 07.10.2015



Seite: 2 von 2

commercial type: **FIAT DUCATO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
250	e3*2007/46*0044*..	96 -130	215/75R16C		*); long wheel base; 1); 2); 33)
			225/75R16C		
250	e3*2007/46*0049*..	96 -130	215/75R16C		*); long wheel base; 1); 2); 33)
			225/75R16C		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 180 Nm

commercial type: **BOXER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0045*..	96 -130	215/75R16C		*); long wheel base; 1); 2); 33)
			225/75R16C		
Y	e3*2007/46*0050*..	96 -130	215/75R16C		*); long wheel base; 1); 2); 33)
			225/75R16C		

commercial type: **PEUGEOT BOXER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2001/116*0233*..	74 -130	215/75R16C		*); not short wheel base; 1); 2); 33)
			225/75R16C		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.