

**Prüfbericht 366-0138-16-WIRD
zur Erteilung der ECE (E1) 124R- 001048**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655115-66

Stand: 05.04.2016



Seite: 1 von 3

Manufacturer : GM DAEWOO (ROK), GM KOREA (ROK), GMC, OPEL, OPEL / VAUXHALL

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 41

Hole circle (mm)/number of holes : 115/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1777	R1-1777	Without	70		670	2025	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : GM DAEWOO (ROK), GM KOREA (ROK)

Mounting parts : conical collar nut M12x1,5

Tightening torque for fixing parts : 140 Nm

commercial type: **CHEVROLET CRUZE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
KL1J	e4*2001/116*0140*..	92 -120	205/60R16		1); 2); 33)
		96 -120	215/60R16		
KL1J	e4*2001/116*0140*..	81	205/60R16		1); 2); 33)
			215/60R16		
		92 -120	205/60R16		
		96 -120	215/60R16		

commercial type: **J309, ORLANDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
CHIO	e50*2007/46*0050*..	104	215/60R16 95V		1); 2); 33)
KL1Y	e4*2007/46*0224*..	96 -120	215/60R16 95V		1); 2); 33)
KL1YN	e4*2007/46*0295*..	120	215/60R16 95V		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : GMC

Mounting parts : conical collar nut M12x1,5

Tightening torque for fixing parts : 140 Nm

commercial type: **Volt**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
D1JCI	e13*2007/46*1158*..	111	205/60R16 96 M+S		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Prüfbericht 366-0138-16-WIRD
zur Erteilung der ECE (E1) 124R- 001048

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655115-66

Stand: 05.04.2016



Seite: 2 von 3

Scope/Vehicle Manufacturer : OPEL, OPEL / VAUXHALL

Mounting parts : conical collar nut M12x1,5

Tightening torque for fixing parts : 125 Nm for Type : P-J; P-J/V
 140 Nm for Type : D1JOI; P-J/SW; P-J/SW/V

commercial type: **AMPERA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
D1JOI	e13*2007/46*1159*..	111	205/60R16 96 M+S		1); 2); 33)

commercial type: **AST/GTC, ZAFIRA, CASCADA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J/SW	e4*2007/46*0204*..	74 -92	205/55R16 91H		*); Only ASTRA SPORTS TOURER; 1); 2); 33)
		74 -96	215/60R16 95H		
		74 -132	205/60R16 92 M+S		
			205/60R16 92V		
			205/65R16 95V		
215/60R16 95V					

commercial type: **ASTRA, ASTRA NOTCHBACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J	e1*2007/46*0141*..	81 -96	215/60R16 95H		*); notchback; 1); 2); 33)
		81 -132	205/60R16 92V		
			205/65R16 95V		
		125 -132	215/60R16 95V		
P-J	e1*2007/46*0141*..	81 -96	205/55R16 91H		*); Hatchback; 1); 2); 33)
			215/60R16 95H		
		81 -132	205/60R16 92 M+S		
			205/60R16 92V		
			205/65R16 95V		
215/60R16 95V					

commercial type: **ASTRA SPORTS TOURER/ZAFIRA TOURER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J/SW/V	e4*2007/46*0308*..	81 -96	205/55R16		*); Only ASTRA SPORTS TOURER; 1); 2); 33)
			205/60R16		
			205/65R16		
		81 -100	215/60R16		
92	205/60R16 M+S				
P-J/SW/V	e4*2007/46*0308*..	81 -110	215/60R16		*); Only ZAFIRA TOURER; 1); 2); 33)

Prüfbericht 366-0138-16-WIRD
zur Erteilung der ECE (E1) 124R- 001048

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655115-66

Stand: 05.04.2016



Seite: 3 von 3

commercial type: **ASTRA VAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J/V	e4*2007/46*0309*..	81 -96	205/55R16 91H		1); 2); 33)
			205/60R16 92		
			M+S		
			205/60R16 92V		
			205/65R16 95V		
			215/60R16 95H		
			215/60R16 95V		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.