

**Prüfbericht 366-0385-15-WIRD
zur Erteilung der ECE (E1) 124R- 001058**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 26.11.2015



Seite: 1 von 1

Manufacturer : **HYUNDAI MOTOR (IND), KIA**

Wheel dates:

Wheel size according to standard : 5 J X 14 H2 Off set(mm) : 46
Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1571	R1-1571	Without	54		420	1726	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **HYUNDAI MOTOR (IND)**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **HYUNDAI I10**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PA	e4*2001/116*0131*..	49 -63	165/60R14 75		1); 2); 33)
			165/60R14 75		
			175/60R14-79H		
PAG	e11*2001/116*0357*..	47 -57	165/60R14 75		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **KIA**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **PICANTO, SA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BA	e4*2001/116*0085*..	44 -48	165/60R14		1); 2); 33)
		55	175/60R14		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.