

**Prüfbericht 366-0006-16-WIRD  
zur Erteilung der ECE (E1) 124R- 001064**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 14604098-6

Stand: 14.01.2016



Seite: 1 von 1

**Manufacturer** : FIAT**Wheel dates:**

Wheel size according to standard : 6 J X 14 H2

Off set(mm) : 40

Hole circle (mm)/number of holes : 98/4

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1638	R1-1638	Without	58		470	1818	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm for Type : 843  
100 Nm for Type : 350commercial type: **FIAT IDEA, MUSA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
350	e3*2001/116*0153*..	51 - 70	185/65R14 86		1); 2); 33)

commercial type: **LANCIA YPSILON**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
843	e3*2001/116*0149*..	44 - 77	185/65R14 86		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.