

**Prüfbericht 366-0018-16-WIRD
zur Erteilung der ECE (E1) 124R- 001065**

ANLAGE: 9.1
Hersteller: MW Aftermarket Srl

Radtyp: 13404100-9
Stand: 19.01.2016



Seite: 1 von 2

Manufacturer : HYUNDAI MOTOR (IND), KIA

Wheel dates:

Wheel size according to standard : 4.00 B X 13 H2 Off set(mm) : 46
Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1572	R1-1575	Without	54		375	1671	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : HYUNDAI MOTOR (IND)

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **HYUNDAI I10**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PA	e4*2001/116*0131*..	49 -63	155/70R13 75		*) ; manual gearbox; not diesel engine; 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : KIA

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **Picanto or Morning**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
TA	e4*2007/46*0256*..	51 -63	155/70R13		*) ; up to e4*2007/46*0256*08; 1); 2); 33)

commercial type: **PICANTO, SA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BA	e4*2001/116*0085*..	44 -48	155/70R13 75		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments

**Prüfbericht 366-0018-16-WIRD
zur Erteilung der ECE (E1) 124R- 001065**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 13404100-9

Stand: 19.01.2016



Seite: 2 von 2

- as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.